


**EMT SET SCREW COUPLINGS**

Set Screw Couplings Steel

B04



Catalog #: 2026

APPLICATIONS

For use in dry locations to couple two ends of EMT conduit. RACO set screw couplings provide concrete-tight connections when taped. RACO set screw couplings are suitable for applications above 600V.
N/A

PRODUCT FEATURES

All steel construction insures mechanical protection for the raceway
Tri-head screws (1/2 in. to 2 in. trade sizes) may be installed using a slotted, Phillips, or Robertson head screwdriver
2-1/2 in. to 4 in. trade sizes are also UL listed for use on Rigid/IMC conduit, allowing for design and installation flexibility
All components are zinc electroplated for corrosion protection
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

UL LISTED

2-1/2" - 4" Standard 514B, File E195969, E195970

CULUS

1/2" - 2" Standard 514B, C22.2 # 18

GENERAL PRODUCT INFORMATION

Trade Size: 1-1/2 in.

DRAWING DIMENSIONS

Dimension A:	3.38 in.
Dimension B:	1.93 in.
Thread Spec. C:	1/4-28UNS

PACKAGING

Package Type:	Carton
Ship Carton Qty.:	20
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	50.80
Ship Carton Length (in.):	10.17
Ship Carton Width (in.):	8.24
Ship Carton Height (in.):	3.97
Pallet Qty:	3600
UPC Number:	050169020265