



KDER.E90057 Grounding and Bonding Equipment

[Page Bottom](#)

Grounding and Bonding Equipment

[See General Information for Grounding and Bonding Equipment](#)

L H DOTTIE CO

E90057

6131 S GARFIELD AVE
CITY OF COMMERCE, CA 90040 USA

Ground clamps for making connection between No. 4, 6 or 8 Awg wire and 1/2, 3/4, or 1-in. ground pipe, rigid conduit or grounding electrode.

Ground clamps for making connection between No. 4, 6 or 8 Awg wire and 1 1/4, 1-1/2 or 2-in. ground pipe, rigid conduit or grounding electrode.

Protective type ground clamps for making connection between armor of No. 4, 6 or 8 Awg bare armored conductor and 1/2 in. rigid conduit.

Protective type ground clamps for making connection between armor of No. 4, 6 or 8 Awg bare armored conductor and 1/2, 3/4 and 1-in. pipe.

Protective type ground clamps for making connection between armor of No. 4, 6 or 8 Awg bare armored conductor and 1-1/4, 1-1/2, and 2-in. pipe.

Ground rod clamps for direct burial. Sizes 1/2 in. through 3/4 in. Cat. Nos. GR-12, -34, -58.

Bronze ground clamps for bare wire, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2 in. through 6 in. Cat. Nos. 25, 27, 250, PL25, 1001, 1002, DB-25, -27 for direct burial.

Bronze ground pipe clamps for bare or armored wire, for making connection between bare or armored wire and galvanized water pipe. Sizes 1/2 in. through 4 in. Cat. Nos. 26, 28, 26SWV.

Ground clamps for rigid conduit, brass body, Cat. Nos. 29, 30, 31, 270, 271, 272.

Grounding bushings, Cat. Nos. GB, GBL-50, -75, -100, -125, -150, -200, -250, -300, -350, -400.

Grounding clip for connecting bare copper or aluminum grounding conductor of nonmetallic sheathed cable to an outlet box and for connecting hump from a receptacle to an outlet box, Cat. No. GC.

Bronze ground pipe clamps for rigid conduit or intermediate metallic conduit, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2 in. through 4 in. Cat. Nos. 29H, 30H, 31H, 270H, 271H, 272H, 280H, 281H, 282H, 290L, 291L, 292L, 29L-BB, 30L-BB, 31L-BB.

Conduit hubs, sizes 1/2 in. through 1 in. Cat. Nos. HUB-50L, -75L, -100L.

Ground bushings, zinc, with 150 C rated nylon insulator and aluminum lug. Sizes 1/2 in. through 4 in. Cat. Nos. GB-50, -75, -100, -125, -150, -200, -250, -300, -350, -400.

Ground bushings, zinc with 150 C rated nylon insulator and C-Clamp lay-in lug. Sizes 1/2 in. through 4 in. Cat. Nos. GBL-50, -75, -100, -125, -150, -200, -250, -300, -350, -400.

Bronze ground pipe clamp for bare wire, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2 in. through 1 in. Also for steel rebar sizes 5 and 6. For direct burial in earth and concrete. Cat. No. DB-25.

Grounding electrodes, Cat. Nos. GR5808, -3410, -1208, -5810, -3408.

Ground bushings, zinc, Cat. Nos. GB400, GB350, GB300, GB250, GB200, GB150, GB125, GB100, GB75, GB50, GBL400, GBL350, GBL300, GBL250, GBL200, GBL150, GBL125, GBL100, GBL75, GBL50.

Grounding lock nut, Cat. No. WTHGN75.

Grounding hubs, Cat. Nos. WTHGL75, WTHGL400, WTHGL350, WTHGL300, WTHGL250, WTHGL200, WTHGL150, WTHGL125, WTHGL100, WTHGL50.

Grounding clamps, Models GR58, UGRC, DL125.

Bronze ground pipe clamps, for bare or armored wire, for making connection between bare or armored wire and galvanized water

pipe. Sizes 1/2 in. through 4 in. Cat. No. LH-C22JA for direct burial.

Bronze ground pipe clamps, for bare wire, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2 in. through 6 in. Also for steel rebar sizes 5 and 6. For direct burial in earth and concrete Cat. No. LH-RBC1D.

Bronze ground pipe clamps, for bare wire, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2 in. through 1 in. Also for steel rebar sizes 5 and 6. For direct burial in earth and concrete. Cat. No. LH-RBC1D.

Bronze ground pipe clamp, for bare wire, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2 in. through in. Also for steel rebar sizes 3, 4, 5, 6 and 8. For direct burial in earth and concrete, Cat. No. LH-RBC1D.

Bronze ground pipe clamps, for rigid conduit or intermediate metallic conduit, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2 in. through 4 in. Cat. No. LH-C11DLH1D.

Last Updated on 2014-02-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".