


Market Products Specification

FINISH - BROWN			FINISH - STAINLESS STEEL			CONNECTION TYPE	WATTS	BTU'S	VOLTS	AMPS	Qtz. Tube Repl. Element	WT. (LBS.)	
Includes Electrical Enclosure													
UPC# 686334	MODEL	LIST	UPC# 686334	MODEL	LIST								
480444	OCH-46-120VE	315	480529	OCH-46-120V-SSE	370	Hard Wire	1500	5120	120	12.5	671-3784	10	
480451	OCH-46-208VE		480536	OCH-46-208V-SSE			2000	6826	208	9.6	671-5061		
480468	OCH-46-240VE		480543	OCH-46-240V-SSE			2000	6826	240	8.3	671-3785		
480475	OCH-46-277VE		480550	OCH-46-277V-SSE			2000	6826	277	7.2	671-5018		
480499	OCH-57-208VE		480574	OCH-57-208V-SSE			3000	10239	208	14.4	671-5060		
480482	OCH-57-240VE	360	480567	OCH-57-240V-SSE	3000		10239	240	12.5	671-3786	12		
480505	OCH-57-277VE		480581	OCH-57-277V-SSE	3000		10239	277	10.8	671-5059			
480512	OCH-57-480VE		480598	OCH-57-480V-SSE	2250		7679	480	4.7	671-5058			
485975	OCH-46-120VCE		340	---	---		---	Corded	1500	5120		120	12.5
485982	OCH-57-208VCE	400	---	---	---		2000		6826	208	9.6	671-5061	13
485999	OCH-57-240VCE		---	---	---	2000	6826		240	8.3	671-3785		

SUBMITTAL DATA, OCH SERIES

AGENT	PROJECT		ENGINEER		DATE
TAG					
QTY.					
MODEL					
LENGTH					
WATTS					
VOLTS / PHASE					
OPTIONS					
NOTES					



Manufactured in U.S.A.

MOUNTING CLEARANCES

- 3" from ceiling
- 12" from vertical surface
- 36" from another heater
- 72" from face of heater to combustible surface

- Frosted Quartz Tube heating element (included)
- Listed for suspended, totally exposed (outdoor) and indoor spot heating applications
- Finish: High-temp brown powder coated finish or corrosion resistant stainless steel 24 gauge housing
- 60° Symmetric Heat Pattern
- Gold anodized Aluminum reflector and end caps
- Painted models are direct wire, unless specified and are supplied with 6" lead wires for field connection in the internal wiring compartment. These models are available with a factory installed 6' cord set. The 208V model must have a field supplied plug.
- Stainless steel models include an electrical enclosure assembled to the end of the heater housing and (2) 6" long lead wires for direct field connection.
- Two 2' ft. long mounting chains and four S-Hooks included
- The OCH-Series can be surfaced mounted using the supplied mounting brackets which allow up to a 45° horizontal tilt adjustment.
- Three different mounting options are available:
 - Chain Mount (supplied, as shown)
 - Wall Mount
 - Ceiling Mount