


# Quik-Splint

## GEN I and III with Chain Assembly

With the Quik Splint installed, less equipment & personnel is required for pole change out. Plus it quickly pays for itself compared to lost revenue of outage.

Calculations were done on 55' poles at ground level. Will fit taller poles

Part #	Part Description	Diameter Range
<b>GEN I</b> 17.2400.00	<ul style="list-style-type: none"> <li>• Comes with chain assembly</li> <li>• Approximate weight per half 65 lbs</li> <li>• Dimensions 6' x 15 3/4"</li> <li>• Material thickness 10 ga (.140)</li> </ul>	Fits Minimum of 9" Diameter  Fits Maximum of 13" Diameter
<b>GEN III</b> 14.0300.00	<ul style="list-style-type: none"> <li>• Comes with chain assembly</li> <li>• Approximate weight per half 85 lbs</li> <li>• Dimensions 6' x 17"</li> <li>• Material thickness 9 ga (.156)</li> </ul>	Fits Minimum of 10" Diameter  Fits Maximum of 18" Diameter
<div>  <p>SEE THESE SPECIALTY TOOLS IN ACTION AT <b>PreciseMachineWorks.com</b></p> </div> <div> <p>Contact your local Irby Sales Representative for details.</p> </div>		



BEFORE



AFTER

