

GRC LARGE RADIUS 90° ELBOWS

TRADE SIZE	METRIC DESIGNATOR	RADIUS		OFFSET		STRAIGHT		APPROXIMATE WEIGHTS PER 100 PIECES	
		IN	MM	IN	MM	IN	MM	LB	KG
1	27	12	305	20-5/8	524	8-5/8	219	483	219.1
1	27	15	381	24-1/4	616	9-1/4	235	564	255.8
1	27	18	457	27-7/8	708	9-7/8	251	644	292.1
1	27	24	610	34-5/8	879	10-5/8	270	792	359.3
1	27	30	762	41	1041	11	279	926	420.0
1	27	36	914	46-3/4	1187	10-3/4	273	1047	474.9
1	27	42	1067	54	1372	12	305	1208	547.9
1	27	48	1219	61-1/4	1556	13-1/4	337	1369	621.0
1-1/4	35	12	305	20-5/8	524	8-5/8	219	654	296.7
1-1/4	35	15	381	24-1/4	616	9-1/4	235	763	346.1
1-1/4	35	18	457	27-7/8	708	9-7/8	251	872	395.5
1-1/4	35	24	610	34-5/8	879	10-5/8	270	1072	486.3
1-1/4	35	30	762	41	1041	11	279	1254	568.8
1-1/4	35	36	914	46-3/4	1187	10-3/4	273	1417	642.8
1-1/4	35	42	1067	54	1372	12	305	1635	741.6
1-1/4	35	48	1219	61-1/4	1556	13-1/4	337	1853	840.5
1-1/2	41	12	305	20-5/8	524	8-5/8	219	789	357.9
1-1/2	41	15	381	24-1/4	616	9-1/4	235	921	417.8
1-1/2	41	18	457	27-7/8	708	9-7/8	251	1052	477.2
1-1/2	41	24	610	34-5/8	879	10-5/8	270	1293	586.5
1-1/2	41	30	762	41	1041	11	279	1512	685.8
1-1/2	41	36	914	46-3/4	1187	10-3/4	273	1710	775.7
1-1/2	41	42	1067	54	1372	12	305	1973	895.0
1-1/2	41	48	1219	61-1/4	1556	13-1/4	337	2236	1014.2
2	53	15	381	24-1/4	616	9-1/4	235	1225	555.7
2	53	18	457	27-7/8	708	9-7/8	251	1400	635.0
2	53	24	610	30-3/8	772	6-3/8	162	1473	668.2
2	53	30	762	41	1041	11	279	2013	913.1
2	53	36	914	46-3/4	1187	10-3/4	273	2275	1031.9
2	53	42	1067	54	1372	12	305	2625	1190.7
2	53	48	1219	61-1/4	1556	13-1/4	337	2975	1349.5
2-1/2	63	18	457	24-3/8	619	6-3/8	162	1910	866.4
2-1/2	63	24	610	31-1/8	791	7-1/8	181	2422	1098.6
2-1/2	63	30	762	37-1/2	953	7-1/2	191	2888	1310.0
2-1/2	63	36	914	44-3/4	1137	8-3/4	222	3447	1563.6
2-1/2	63	42	1067	54	1372	12	305	4193	1901.9
2-1/2	63	48	1219	61-1/4	1556	13-1/4	337	4752	2155.5
3	78	15	381	24-1/4	616	9-1/4	235	2545	1154.4
3	78	18	457	24-3/8	619	6-3/8	162	2484	1126.7
3	78	24	610	33-1/8	841	9-1/8	232	3393	1539.1
3	78	30	762	38-5/8	981	8-5/8	219	3892	1765.4
3	78	36	914	46-7/8	1191	10-7/8	276	4741	2150.5
3	78	42	1067	54	1372	12	305	5453	2473.5
3	78	48	1219	60-1/4	1530	12-1/4	311	6058	2747.9
3	78	60	1524	75-7/8	1927	15-7/8	403	7634	3462.8
3-1/2	91	18	457	26-3/8	670	8-3/8	213	3300	1496.9
3-1/2	91	24	610	35-1/8	892	11-1/8	283	4400	1995.8
3-1/2	91	30	762	38-1/2	978	8-1/2	216	4693	2128.7
3-1/2	91	36	914	47	1194	11	279	5757	2611.4
3-1/2	91	42	1067	54	1372	12	305	6600	2993.8
3-1/2	91	48	1219	60-1/4	1530	12-1/4	311	7333	3326.2
4	103	18	457	27-3/8	695	9-3/8	238	4034	1829.8
4	103	24	610	35-1/8	892	11-1/8	283	5150	2336.0
4	103	30	762	39-3/8	1000	9-3/8	238	5644	2560.1
4	103	36	914	47	1194	11	279	6738	3056.4
4	103	42	1067	54	1372	12	305	7725	3504.1
4	103	48	1219	60-1/4	1530	12-1/4	311	8583	3893.2
4	103	60	1524	75-7/8	1927	15-7/8	403	10815	4905.7
5	129	36	914	50-3/4	1289	14-3/4	375	10033	4551.0
5	129	48	1219	65-1/4	1657	17-1/4	438	12833	5821.0
5	129	60	1524	75-7/8	1927	15-7/8	403	14700	6667.9
6	155	36	914	50-3/4	1289	14-3/4	375	13187	5981.6
6	155	48	1219	65-1/4	1657	17-1/4	438	16867	7650.9
6	155	60	1524	75-7/8	1927	15-7/8	403	19320	8763.6