

Rigid and intermediate metal conduit fittings

Hubs



Nylon insulated

Aluminum, steel or malleable iron (steel through 1 in.). With neoprene O-ring provides a watertight threaded hub on enclosures. UL Listed 105 °C.

Steel/malleable iron and aluminum hub fittings†



Diagram	Cat. no.		Size (in.)	Dimensions (in.)			Wall thk. max. (in.)
	Stl. or M.I.	Alum.**		A	B	C	
	370	370AL	½	1⅞	1⅞	¾	⅝
	371	371AL	¾	1⅞	1⅞	⅞	⅝
	372	372AL	1	2⅜	1⅞	1⅞	⅝
	373	373AL	1¼	2⅞	2	1⅞	⅝
	374	374AL	1½	3⅜	2	1⅞	⅝
	375	375AL	2	3⅞	1⅞	1⅞	⅝
	376	—	2½	4⅞	2⅞	1⅞	⅝
	377	—	3	5	2⅞	2	½
	378	—	3½	5⅞	3⅞	2⅞	½
	379-TB	—	4	6⅞	3⅞	2⅞	½
	381-TB	—	5	8	4	2⅞	½
	382-TB	—	6	9⅞	4	2⅞	½

** Aluminum not available with insulated throat

† UL Listed raintight and CSA Certified watertight and dust tight



Bullet hub fittings with bonding locknut – Nylon insulated



Cat. no.	Size (in.)	Description
401	½	Available in steel or malleable iron Supplied with 106 Series bonding nut. Temperature rating: 105 °C.
402	¾	
403-TB	1	
407	2½	
408	3	
409	3½	
410-TB	4	

CSA certified watertight and dust tight