



SPECIFICATIONS

BFQ90

EXHAUST FANS



90 CFM/3.0 Sones @ 0.10" SP.

• Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10³/₄" x 11⁵/₈".

• Blower Wheel

One piece polymeric wheel 5¹/₈" diameter, 2³/₈" wide, with 48 fins.

• Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

• Fan Housing

PC/ABS polymeric, dimensions 8³/₄" x 9" x 4³/₄".

• Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

• Ventilating Area


For bathrooms up to 90 sq. ft. For other rooms up to 115 sq. ft.

• Single Pack Shipping Info

Box Dim: 11¹/₈" x 12" x 6³/₈"

UPC: 0-8316290320-4

Shipping Weight: 5¹/₄ lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.



• Unit Mounting

Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 8⁷/₈" x 9¹/₈".

EXPANDED PERFORMANCE

	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	101	95	90	88	85	81	74	3.0	1375	50	0.7

PROJECT							ARCHITECT				
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY			DATE	
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



U.S.: 820 Lincoln Avenue
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 • 877-304-3785
Fax: (610) 696-8048

Canada:
Bolton, Ontario
Tel: 905-456-2033