



Patented Malleable Liquidtight Screw On 90° Connectors

Innovative electrical fittings with premium quality and service offering more than 1,600 SKUs and numerous labor savings products

Features

- No disassembly required for installation
- Long ferrule prevents pullout and tight bend conduit pop-out
- Liquidtight/Raintight/Oiltight
- Compact, slim diameter

Standard Materials

- Malleable Iron

Standard Finish

- Zinc Plated

Applicable Third Party Standards

- CULUS 514B, File Number: E207875
- NEMA FB-1
- Patent #: US 7,914,048



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Dim C (in)	Dim D (in)	Box	Case	Weight Per C (lb)	Insulated
LTQ3890KON	3/8	1.31	0.50	1.13	1.63	25		25	No
LTQ3890-ICKON	3/8	1.31	0.56	1.13	1.63	25		26	Yes
LTQ5090KON	1/2	1.44	0.50	1.25	1.63	25		29	No
LTQ5090-ICKON	1/2	1.44	0.56	1.25	1.63	25		29	Yes
LTQ7590-ICKON	3/4	1.63	0.56	1.56	1.75	10		45	Yes
LTQ7590KON	3/4	1.63	0.50	1.56	1.75	10		44	No
LTQ10090KON	1	2.31	0.63	1.81	2.13	10		75	No
LTQ10090-ICKON	1	2.31	0.69	1.81	2.13	10		75	Yes
LTQ12590KON	1 1/4	2.88	0.69	2.25	2.19	4	40	96	No
LTQ12590-ICKON	1 1/4	2.88	0.75	2.25	2.19	4	40	97	Yes
LTQ15090KON	1 1/2	2.69	0.75	2.44	2.50	3	30	122	No
LTQ15090-ICKON	1 1/2	2.69	0.81	2.44	2.50	3	30	123	Yes
LTQ20090-ICKON	2	3.19	0.81	3.00	2.88	2	20	178	Yes
LTQ20090KON	2	3.19	0.75	3.00	2.88	2	20	176	No