

ETP™ 6000S Steel EMT Compression Couplings

NEC/CEC:
Listed for Ordinary Locations

Application

- To ground and secure EMT raceway sections together.

Features

- Concretetight.
- Raintight (wet locations) Canada.

Material/Finish

- Body and nut: steel.
- Steel/zinc plated

NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- cUL Listed: E-14895, E14815
- CSA Certified: 009795
- NEMA: FB-1



6050S – 6400S

Trade Size (Inches)	Dimensions in Millimeters (Inches)		Weight per 100 kg (lb)	Catalog Number
	Body Length	Maximum Diameter		
1/2	35.1 (1.38)	21.3 (0.84)	8.6 (19.00)	6050S
3/4	38.1 (1.50)	35.1 (1.38)	11.3 (25.00)	6075S
1	42.2 (1.66)	33.3 (1.31)	17.7 (39.00)	6100S
1-1/4	63.5 (2.50)	42.9 (1.69)	39.9 (88.00)	6125S
1-1/2	63.5 (2.50)	49.3 (1.94)	47.2 (104.00)	6150S
2	63.5 (2.50)	60.5 (2.38)	67.6 (149.00)	6200S
2 - 1/2	94.0 (3.70)	74.4 (2.93)	108.9 (240.00)	6250S
3	110.7 (4.36)	90.4 (3.56)	158.8 (350.00)	6300S
3 - 1/2	124.2 (4.89)	103.1 (4.06)	215.5 (475.00)	6350S
4	130.8 (5.15)	115.8 (4.56)	272.2 (600.00)	6400S