

Flexible Fixture Hangers

Hook and Loop

UNILETS® for Use with Threaded Rigid Metal Conduit and IMC.

Applications

- Designed for suspension of HID, fluorescent and incandescent lighting fixtures.

Features

- Protect fixture against wind and vibration damage.
- Cushion type for added protection where lighting fixtures are subjected to vibration.
- EF hook and loop hangers
 - Malleable iron for strength and safety.
 - Hook and loop combination permits quick disconnect and removal of fixture for maintenance.
 - Offer inexpensive means of pendant flexible suspension of lighting fixtures.
 - Permit free swing in any direction.
 - EF jaw openings can be completely closed for added safety.
- FHS support hangers
 - Provide up to 350 lbs/158.8kg support for fluorescent fixtures on the non-electrical side of mounting.
 - Straddle a maximum of 1-1/4" conduit and take 1/2" or 3/4" fixture hook or conduit.

Standard Materials

- Malleable iron



EFHM



EFHF





FHS

Standard Finishes


- Zinc electroplate and clear chromate

Certifications and Compliances

- CSA Certified: 065180

	Size (Inches)	Length A (in/mm)	Support Weight Lbs./Kg.	Catalog Number
EF — Safety Support Hooks — With 3/8" jaw opening				
	EFHM — Male			
	1/2	2.63/66.8	200/90.0	EFHM-50
	3/4	2.94/74.7		EFHM-75
	EFHF — Female			
	1/2	2.00/50.8	200/90.0	EFHF-50
	3/4	2.05/52.1		EFHF-75
FHS — Support for Fixtures, Dummy Side — Straddles up to 1-1/4 trade size conduit — 11/32" diameter mounting holes, spaced 3-1/4" apart				
	1/2 or 3/4	3.31/87.1	350/157.5	FHS5075

Dimensions in Inches/Millimeters

	A	B	C	Catalog Number
	1/2-14 NPT	2.00/50.8	2.63/66.8	EFHM-50
	3/4-14 NPT	2.13/54.1	2.88/73.2	EFHM-75
	1/2-14 NPT	2.00/50.8	N/A	EFHF-50
	3/4-14 NPT	2.13/54.1	N/A	EFHF-75