



Slots are $1\frac{1}{8}$ " (29) x $\frac{9}{16}$ " (14)
2" (51) on Center

P1100T - 1-5/8" x 1-5/8", 14 Gauge, Slotted

14 Gauge Slotted Strut Channel P1100T is the original metal framing strut channel and has been used in countless applications for over 90 years. Commonly known as 14 Gauge Standard or Deep Slotted Channel, it is the global standard for strut metal framing.

Features

- OPM pre-approved for seismic applications
- Slots are sized for a 1/2" threaded rod or fastener
- Product dimensions are 15/8" wide x 15/8" tall x 14 ga. thick.
- Our P1100T is available in Pre-Galvanized (PG), Atkore Defender (DF), Hot-Dip Galvanized (HG), Plain (PL), Green (GR), Zinc Dichromate (ZD), Stainless Steel (SS or ST) and Aluminum (EA).
- Made in the USA

Standard Lengths:

- **10 feet:** 10' or $10\frac{1}{8}$ " (3.05m) $\pm \frac{1}{8}$ " (3 mm)
- **20 feet:** 20' or $20\frac{3}{8}$ " (6.11m) $\pm \frac{1}{8}$ " (3 mm)

Special Lengths:

- Available with a tolerance of $\pm \frac{1}{8}$ " (3 mm). Request quote.

Curved Channel:

- Many Unistrut channel sections can be supplied with a curve. Click here for our ordering form, specifications, and instructions.

Load Data:

- All beam and column load data pertains to carbon steel and stainless steel channels.
- Load tables apply only to UNISTRUT brand channel. Look for "UNISTRUT" on the product.
- Load tables and charts are constructed to be in accordance with the SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS 2007 EDITION published by the AMERICAN IRON AND STEEL INSTITUTE USING ASD METHOD.
- Loads are based on 33 ksi steel cold formed to 42 ksi.
- Safety Factor to Yield Strength is 1.67 for Beam Loads and 1.80 for Column Loads.
- Beam loads are based on a simple beam and are given as a total uniform load (W) in pounds. For proper calculation procedures, refer to our Beam Load Calculation Guide under Resources.
- For bearing loads, reference our Bearing Loads Page.

Materials & Finishes - Standard:

- **Pregalvanized (PG):** Conforms to ASTM A653 SS GR 33, G90.
- **Unistrut Defender (DF):** Conforms to ASTM A1046 SS GR 33
- **Hot Dip Galvanized (HG):** Steel conforms to ASTM A1011 SS GR 33, Finish conforms to ASTM A123
- **Perma-Green (GR):** Steel conforms to ASTM A1011 SS GR 33, E-Coat finish
- **Perma-Gold (ZD):** Steel conforms to ASTM A1011 SS GR 33, Finish conforms to ASTM B633, Type II SC3
- **Plain (PL):** Conforms to ASTM A1011 SS GR 33

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** ASTM A240, Type 304 *
- **Stainless Steel, Type 316 (ST):** ASTM A240, Type 316 *
- **Aluminum (EA):** ASTM B221, Type 6063-T6 (Extruded) *

* These materials have different physical properties and performance characteristics. Please contact us for design support.



Catalog Number	Length (ft)	Gauge	Material Type	Surface Finish	Part Weight (lb/ft)	Standard Package Qty (ft)	Standard Package Weight (lb)
P1100T 10GR	10	14	Steel	Green E-Coat	1.4	500	700
P1100T 10HG	10	14	Steel	Hot-Dip Galvanized	1.36	500	680
P1100T 10PG	10	14	Steel	Pre-Galvanized	1.36	500	680
P1100T 10PL	10	14	Steel	Plain/Oil	1.36	500	680
P1100T 10SS	10	14	Stainless Steel - 304		1.36	500	680
P1100T 10ZD	10	14	Steel	Zinc Dichromate	1.4	500	700
P1100T 20GR	20	14	Steel	Green E-Coat	1.4	1000	1400
P1100T 20HG	20	14	Steel	Hot-Dip Galvanized	1.36	1000	1360
P1100T 20PG	20	14	Steel	Pre-Galvanized	1.36	1000	1360
P1100T 20PL	20	14	Steel	Plain/Oil	1.36	1000	1360
P1100T 20SS	20	14	Stainless Steel - 304		1.36	1000	1360

Beam Loading - P1100T						
Span (in)	Max Allowable Uniform Load (lbs)	Deflection at Uniform Load (in)	Uniform Loading at Deflection			Lateral Bracing Reduction Factor
			Span/180 (lbs)	Span/240 (lbs)	Span/360 (lbs)	
24	1,148	0.06	1,148	1,148	1,148	1.00
36	765	0.13	765	765	595	0.89
48	578	0.23	578	502	340	0.78
60	459	0.36	434	323	213	0.68
72	383	0.51	298	221	153	0.59
84	332	0.70	221	162	111	0.52
96	289	0.92	170	128	85	0.47
108	255	1.15	136	102	68	0.43
120	230	1.42	111	77	51	0.40
144	196	2.09	77	60	34	0.36
168	162	2.75	51	43	26	0.32
192	145	3.67	43	34	NR	0.30
216	128	4.61	34	26	NR	0.28
240	119	5.90	26	NR	NR	0.26
Note	NR - Not Recommended					

Refer to the General Specifications for loading information.

Column Loading - P1100T				
Unbraced Height (in)	Allowable Load at Slot Face (lbs)	Max Column Load Applied at C.G.		
		K=0.65 (lbs)	K=0.80 (lbs)	K=1.0 (lbs)
24	2,800	8,040	7,330	6,360
36	2,410	6,480	5,430	4,190
48	1,940	4,990	3,830	2,760
60	1,550	3,740	2,760	2,050
72	1,290	2,860	2,160	1,640
84	1,100	2,310	1,780	1,370
96	950	1,950	1,520	1,180
108	840	1,690	1,320	1,030
120	760	1,490	1,180	KL/r>200
144	630	1,210	950	KL/r>200

Refer to the General Specifications for loading information.

Elements of Section - P1100T			
Area of Section		0.418 in ² (2.7 cm ²)	
		Axis 1-1	
Moment of Inertia (I)		0.145 in ⁴ (6 cm ⁴)	
Section Modulus (S)		0.162 in ³ (2.7 cm ³)	
Radius of Gyration (r)		0.589 in (1.5 cm)	
		0.65 in (1.7 cm)	