



Standard Dimensions (Unless Shown Otherwise on Drawing):

- **Hole Diameter:** $9/16$ " (14mm)
- **Hole Spacing (From End):** $13/16$ " (21mm)
- **Hole Spacing (On-Center):** $1 7/8$ " (48mm)
- **Width:** $1 5/8$ " (41mm)
- **Thickness:**
- $1/4$ " (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or
- 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

Note:

- When used for mechanical supports, load capacities of brackets and fittings should be in compliance with the American Standard Code for Pressure Piping.

Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please contact us for design support.

P2469 - 2 Hole, "Z" Shape Fitting

Atkore's Z-shape fittings offer strong, versatile support for complex framing configurations, allowing secure connections at varied angles. Engineered for durability and ease of installation, they perform reliably across a wide range of applications.

Features

- Steel: ASTM A1011 SS GR 33
- Holes for 1/2" fasteners
- Variety of material and finish options



Catalog Number	Material Type	Surface Finish	Part Weight (lb/ea)	Standard Package Weight (lb)
P2469 EG	Steel	Electrogalvanized	0.93	23.25
P2469 GR	Steel	Green E-Coat	0.93	23.25
P2469 HG	Steel	Hot-Dip Galvanized	0.99	24.75