



Standard Dimensions (Unless Shown Otherwise on Drawing):

- **Hole Diameter:** $\frac{9}{16}$ " (14mm)
- **Hole Spacing (From End):** $\frac{13}{16}$ " (21mm)
- **Hole Spacing (On-Center):** $1\frac{5}{8}$ " (48mm)
- **Width:** $1\frac{5}{8}$ " (41mm)
- **Thickness:**
- $\frac{1}{4}$ " (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or
- 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

Note:

- When used for mechanical supports, load capacities of brackets and fittings should be in compliance with the American Standard Code for Pressure Piping.

Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please contact us for design support.

P2674 - Beam Clamp

Beam Clamp Pivot Hanger P2674 is to be used when attaching Atkore beam clamps to a sloped or angled beam.

Features

- For sloped or angled beams
- Vertical Design Load: 250 lbs
- Threaded rod sizes up to 3/8"
- This series is available in Electrogalvanized (EG), Hot-Dip Galvanized (HG) and Perma-Green (GR).



| Catalog Number | Material Type | Surface Finish | Part Weight (lb/ea) | Standard Package Weight (lb) |
|----------------|---------------|-------------------|---------------------|------------------------------|
| P2674 EG | Steel | Electrogalvanized | 0.17 | 8.5 |

Design Load = 250 lbs (1.11 kN)

Notes:

1. Design loads only apply to Unistrut brand products. Look for "UNISTRUT" on the part.
2. Use with P2675 beam clamp.
3. Safety factor = 2.5 based on ultimate strength of connection.
4. Rod sizes up to 3/8".