



P2749 - 2 Wheel Trolley

Trolley System provides mobility, reliability and economy. Stainless Steel wheel bearings require no lubrication for longevity and maintenance-free performance. Specialized supports allow trolleys to travel the full length of the strut channel track. Great for doors, tools, curtains and other applications.

Features

- Design Load: 10 - 50 lbs [0.04 - 0.22 kN] per table
- Wheel bearings should not be lubricated
- Mounting hole for 1/4" fastener

Specifications:
· Do not lubricate

Materials & Finishes:
· Electrogalvanized (EG)
· Stainless Steel (SS)
· "N" indicates Acetal wheels



Catalog Number	Material Type	Surface Finish	Part Weight (lb/ea)	Standard Package Weight (lb)
P2749 EG	Steel	Electrogalvanized	0.21	5.25
P2749N EG	Steel	Electrogalvanized	0.13	3.25
P2749 SS	Stainless Steel - 304		0.21	5.25

Design Loads - P2749	
Part Number	Design Load lbs (kN)
P2749	50 (0.22)
P2749N	10 (0.04)

- Notes:**
1. Design loads only apply to Unistrut brand products. Look for "UNISTRUT" on the part.
 2. Safety factor = 2.5 based on the ultimate strength of the connection when mounted to 12 gauge channel.