



## P7006 - Channel Nut W/Spring

Spring Nuts allow for easy installation into Atkore channel. Once inserted into the channel and with a 90° turn, these spring nuts will stay in place allowing hands-free installation of other components.

### Features

- #8 - 1/4" sizes available
- EG coated for corrosion protection
- For use with 13/16" wide channel
- This series is available in Electrogalvanized (EG)

### Threads:

- Threads meet the Unified Screw Thread standard, ANSI B1.1, coarse series (UNC) class 2.
- Channel Nuts are also available in many standard metric sizes. Contact us for ordering information.

### Design Bolt Torque:

- **1/4" Bolt Size:** 6 - 7 ft-lbs (8-9 N-m)

### Materials & Finishes:

- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1 or SC3



Catalog Number	Trade Size	Material Type	Surface Finish	Part Weight (lb/ea)	Standard Package Weight (lb)
P7006-1420EG	1/4 <sup>20</sup>	Steel	Electrogalvanized	0.01	5
P7006-0832EG	#8 <sup>32</sup>	Steel	Electrogalvanized	0.01	5
P7006-0836EG	#8 <sup>36</sup>	Steel	Electrogalvanized	0.01	5
P7006-1024EG	#10 <sup>24</sup>	Steel	Electrogalvanized	0.01	5
P7006-1032EG	#10 <sup>32</sup>	Steel	Electrogalvanized	0.01	5
P7006M1032EG	#10 <sup>32</sup>	Steel	Electrogalvanized	0.01	1