



Introducing new commercial grade strut

Eaton's B-Line Business offers the strength of a 12 gauge strut in a lighter weight design. C22 is available in solid and SH hole patterns and is available in 2 lengths (10 foot and 20 foot). The Commercial Grade Strut offering is compatible with B-Line's diverse offering in strut fittings. C22 is offered in a G90 pre-galvanized finish. For more information, visit www.cooperbline.com/C22.

Span (in)	B-Line	Gregory®† G-Strut®†	Haydon®†	T & B®† Superstrut®†	Unistrut®†
24	Part Number	C22	G-582	H-132	A-1200
	Uniform Load* (lbs)	1813	1610	1740	1766
	Deflection* (in)	0.058	0.050	0.06	0.058

Span (in)	Uniform Load (Lbs.)	Deflection (In.)
12	2780	0.011
24	1813	0.058
36	1209	0.131
48	921	0.237
60	737	0.370
72	614	0.533
84	526	0.725
96	453	0.931
108	403	1.180
120	362	1.454

Material Number	Part Number	Description
12369054	C22-120GLV	Solid, 10' length
12369056	C22-240GLV	Solid, 20' length
12369057	C22SH-120GLV	Slotted (9/16" x 1-1/8" on 2" centers), 10' length
12369058	C22SH-240GLV	Slotted (9/16" x 1-1/8" on 2" centers), 20' length

Dimensions: 1 1/8" x 1 1/8"

Features:

- Strength to Weight Ratio is higher than 12 gauge 1 1/8" x 1 1/8" Strut
- Load ratings are 5% or greater than 12 gauge 1 1/8" x 1 1/8" Strut
- Commercially available
- Available in G90 pre-galvanized finish
- Available in solid and SH hole patterns
- Available in two lengths: 10 foot and 20 foot
- Resistance to slip meets or exceeds 12 gauge listings for 3/8"-16 hardware (3/8" channel nut thickness)
- Pull-out meets or exceeds 12 gauge listing for 1/2"-13 hardware (3/8" channel nut thickness)
- Additional engineering test data available upon request
- Available with B-Line Standard Terms and Conditions

www.cooperbline.com/terms

*All marks shown are properties of their respective owners. Information contained in the above chart for competitive comparison was obtained through the respective websites of the companies listed.

*B-Line has made every effort to ensure the integrity of the contents of this document. However, B-Line cannot accept responsibility for errors, that may have been caused by changing dimensions/part numbers, or for typographical or clerical errors in the preparation of this document. The data and dimensions are provided for reference only. B-Line does not assume responsibility for the selection, use, or maintenance of any product. Responsibility for the proper selection, use, and maintenance of any B-Line product remains solely with the purchaser and end-user. Information is subject to change without notification.

B-Line
by 