



Myers hubs

Stainless steel ATEX high temperature hubs

Applications:

- Myers™ hubs are used in the termination of electrical circuits through wall of the enclosure
- Designed for use indoors or outdoors with rigid conduit and IMC
- Ideal for pharmaceutical, chemical and food processing, pulp/paper, nuclear, solar and commercial construction applications
- Suitable for use in environmentally demanding applications, including those with the presence of chemicals, such as acetic, citric and salt water
- Suitable for use in hazardous (classified) locations

Features and benefits:

- Wide range of styles, trade sizes and materials to meet customer requirements and preferences
- Multiple certifications provide users peace of mind
- Easy installation and smooth pulling service for labor savings
- Tapered female threads for rigid/IMC conduit, NPSM male threads

Certifications and compliances:

NEC/CEC:


- Class I, Zone 1, AEx e II
- Class I, Zone 1, Ex e II

cULus Listed

- UL Standard 514B
- CSA Standard C22.2 No. 18

NEMA Type 2, 3, 3R, 4, 4X

IEC:

- ATEX Certified DEMKO 18 ATEX 2002X,  II 2G Ex eb IIC Gb to EN IEC 60079-0:2018 and EN IEC 60079-7:2015 +A1:2018 standards Ta -55°C to 180°C
- IECEx Certified IECEx UL 18.0007X, Ex eb IIC Gb to IEC 60079-0:2017 and IEC 60079-7:2017 standards Ta -55°C to 180°C
- IP66

Now rated for
-55°C to 180°C



 II 2 G Ex eb IIC Gb Ta (-55°C to 180°C)

IECEx - Ex eb IIC Gb Ta (-55°C to 180°C)

Class I, Zone 1, AEx e II

Class I, Zone 1, Ex e II

Cat. #	Size	Unit Qty.	Max. copper ground wire size	
			CSA‡	UL‡
SSTGK 1 M2	1/2"	10	#8	#8
SSTGK 2 M2	3/4"	10	#8	#8
SSTGK 3 M2	1"	10	#8	#8
SSTGK 4 M2	1 1/4"	5	#8	#8
SSTGK 5 M2	1 1/2"	5	#6	#8
SSTGK 6 M2	2"	5	#4	#8
SSTGK 7 M2**	2 1/2"	2	#2	#6
SSTGK 8 M2**	3"	2	1 / 0	#6
SSTGK 9 M2**	3 1/2"	2	2 / 0	#6
SSTGK 10 M2**	4"	2	2 / 0	#4

‡Use of wire terminal is required by CSA & recommended by UL for wire gauges over 10 AWG.

**Not UL Listed as a means of grounding and bonding.

Standard materials:

- Nut: stainless (316)
- Body: stainless (316)
- Insuliner: PEEK GF15
- O-Ring: silicone
- Ground screw: stainless steel