



DCF900B

20V MAX* XR® 1/2 In. High Torque Impact Wrench with Hog Ring Anvil

- COMPLETE A WIDE VARIETY OF FASTENING APPLICATIONS with 1030 ft.-lbs of max fastening torque and 1400 ft.-lbs of max breakaway torque.
- INCREASE USER CONTROL IN A VARIETY OF APPLICATIONS with 4-mode speed settings and variable speed trigger.
- DESIGNED TO HELP PREVENT OVERTIGHTENING AND FASTENER RUN-OFF with Precision Wrench™ control.



Product Overview

Complete the toughest jobs utilizing the power of the DEWALT 20V MAX* XR® 1/2 in. High Torque Impact Wrench. Delivering 1030 ft.-lbs. of max fastening torque and 1400 ft.-lbs. of max breakaway torque, making it ideal for large sized pipe flanges, grooved couplings, wheel lugs, concrete anchor bolt setting and many other heavy-duty impact wrench applications. The PRECISION WRFNCH™ mode is included to help prevent overtightening in forward and run-off in reverse for additional user control. Utilize the [Read more](#)

Additional Features

- REDUCE WEAR AND TEAR ON THE BATTERY WHILE YOU WORK with BATTERYGUARD™ - a shock-absorbing battery-to-tool connection (battery sold separately).
- ILLUMINATE DARK WORKSPACES using the on-tool LED work light.

Includes

(1) DCF900 Impact Wrench

Specifications

| | |
|----------------------|-------------|
| Battery Type | Lithium-Ion |
| Impact Rate per Min. | 2200 |
| Led light | Yes |

Max Torque

1400 ft-lbs

Power Source

Cordless

Product Height

9.1 in

Product Length

8.8 in

Product Weight

6.4 lbs

Product Width

4.25 in

Voltage

20 V