



PRO-TITE

PRO-TITE THREAD SEALANT – 1-1/3 OZ. SQUEEZE TUBE

Item#: CLL-1

The PRO-TITE® CLL-1 resin based thread sealant adheres to internal surfaces and fills voids while forming a flexible fluid tight seal. Specifically formulated for use on metals and plastics subject to extreme vibration. Serviceable at temperatures from 100°F (73°C) to 400°F (204°C) and from full vacuum to 10,000 PSI. It's impervious to most chemicals including refrigerants, petroleum products, gases, steam, etc. Alcohol based.

Product Features & Benefits

- Impervious to most chemicals including refrigerants, petroleum products, gases, steam, etc.
- Serviceable at temperatures from 100°F (73°C) to 400°F (204°C) and from full vacuum to 10,000 PSI
- Formulated for use on metals and plastics subject to extreme vibration
- Safe for all plastics and metals
- Thread Sealant Squeeze Tube, 1.3 fl oz

Specifications

Color	N/A	Temp. Range	(-100°F (-73°C) to 400°F (204°C))
Container Size	1-1/3 oz.	Ducted or Ductless	Both Ducted and Ductless
Container Type	Tube		

Order Info

UPC	95247086009	Primary Height (inches)	0.75
Primary UoM	Each	Primary Weight (lbs)	0.11
Primary Depth (inches)	5.25	Quick Ship Flag	No
Primary Width (inches)	1.5	Order Multiple	12