

# Specifications



Photo is representative



## Eaton BK/S500-2.5-R

Eaton S500 Series Fast-acting fuse 2.50A, 250 Vac or less, 32 Vdc (self certified), BK-S500-2-5-R

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series S500 fast-acting fuse
<b>CATALOG NUMBER</b>	BK/S500-2.5-R
<b>UPC</b>	051712643382
<b>PRODUCT HEIGHT</b>	20.5 mm
<b>PRODUCT DIAMETER</b>	5.2 mm
<b>PRODUCT WEIGHT</b>	0.7 g
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	CE Marked CCC Marked RoHS Compliant
<b>CERTIFICATIONS</b>	VDE
<b>GLOBAL CATALOG</b>	BK/S500-2.5-R



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	2.50A
<b>FREQUENCY RATING - MAX</b>	50 Hz
<b>FREQUENCY RATING - MIN</b>	50 Hz
<b>VOLTAGE DROP</b>	150 mV maximum
<b>INTERRUPT RATING</b>	35 AIC at 250 Vac
<b>FUSE INDICATOR</b>	Non-indicating
<b>CONNECTION</b>	Ferrule end x ferrule end
<b>MATERIAL</b>	Glass tube Nickel-plated end-cap construction
<b>QUANTITY</b>	100
<b>VOLTAGE RATING</b>	250 Vac or less, 32 Vdc (self certified)
<b>TYPE</b>	Electronic
<b>APPLICATION</b>	Electronic circuits

## Resources

SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - BK/S500-2.5-R</a>
	<a href="#">Eaton S500 glass tube fuses data sheet</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

