

Modular metering factory installed accessories

Factory installed lug kits

Amp rating	Main breaker	Phase wire size	Neutral wire size	Lugs per kit	Total lugs per device	Ordering code
400	TMP5B4R	AL/CU: (2) 2/0-500 or (1) 8-600	AL/CU: (2) 2-600	2	–	TCLK265
	TMP5HB4R			3		TCLK365
	TMP3SB4R					
	TMP3SHB4R					
600	TMP3SB6R	AL/CU: (2) 2/0-500 or (1) 8-600	AL/CU: (2) 2-600	3	–	TCLK365
800	TMP5B8R	AL/CU: (3) 3/0-500	AL/CU: (4) 250-500	1	–	TCAL81 ¹
	TMP3SB8R					
1000	TMP5B10R	AL: (4) 250-500	AL/CU: (4) 250-500	1	–	TCAL125 ²
	TMP3SB10R					
1200	TMP5B12R	AL: (4) 250-500	AL/CU: (4) 250-500	1	–	TCAL125 ²
	TMP3SB12R					
1400	TMPBB14R, TMPBB14RAR	AL/CU: (4) 500-1000	AL/CU: (4) 500-1000	1 lug/kit, 4 holes/lug	3	TMPL1600RD
	TMP3BB14R, TMP3BB14RAR				4	
	TMP3BT14R, TMP3BT14RAR					
1600	TMPBB16R, TMPBB16RAR	AL/CU: (4) 500-1000	AL/CU: (4) 500-1000	1 lug/kit, 4 holes/lug	3	TMPL1600RD
	TMPBB16RST					
	TMPBT16R, TMPBT16RAR					
	TMPBT16RST					
	TMP3BBT16RST					
	TMP3BB16R, TMP3BB16RAR					
	TMP3BT16R, TMP3BT16RAR					
	TMP3BT16RST					
2000	TMPBB20R, TMPBB20RAR	AL/CU: (6) #2-600	AL/CU: (6) #2-600	9	6 lugs/device; 3 lugs/neutral	TMPL2000RD
	TMPBT20R				9 lugs/device; 3 lugs/neutral	
	TMP3BB20R, TMP3BB20RAR					
	TMP3BT20R, TMP3BT20RAR					

¹Lug kits TCALK281 (for TMP5B8R) and TCALK381 (TMP3SB8R) can also be used instead of the TCAL81 lugs

²Lug kits TCALK2125 (for TMP5B10R and TMP5B12R) and TCALK3125 (for TMP3SB10R and TMP3SB12R) can also be used instead of TCAL125 lug

Optional lug kit

Amp rating	Main breaker	Phase wire size	Phase ordering code	Lugs per kit	Neutral product number	Neutral wire size
1000	TMP5B10R	AL/CU: (3) 350-750	TCAL124 ³	2	1	–
	TMP3SB10R			3		
1200	TMP5B12R	AL/CU: (3) 350-750	TCAL124 ³	2	1	–
	TMP3SB12R			3		
1400	TMPBB14R	(6) #2-600	TMPL2000RD	9	TMBP2000N	(6) #2-600
	TMP3BB14R					
	TMP3BT14R					
1600	TMPBB16R	(6) #2-600	TMPL2000RD	9	TMBP2000N	(6) #2-600
	TMP3BB16R					
	TMPBB16RST					
	TMP3BB16RST					
	TMPBT16R					
	TMP3BT16R					
	TMPBT16RST					
	TMP3BT16RST					

³Lug kits TCALK2124 (for TMP5B10R and TMP5B12R) and TCALK3124 (for TMP3SB10R and TMP3SB12R) can also be used instead of TCAL124 lugs