

Meter Mod III

Single phase 800A horizontal bussing 125 & 200A sockets—MEG approved

Socket amps	No. of sockets	Ordering code		
		Ring type socket (4 jaw socket standard)	Ringless type socket (5th jaw socket standard)	Ringless type socket (5th jaw socket standard) horned bypass factory installed
125	2	TMPR8212RF ¹	TMPR8212RF	TMPR8212RHBF
	3	TMPR8312RF ¹	TMPR8312RF	TMPR8312RHBF
	4	TMPR8412RF ¹	TMPR8412RF	TMPR8412RHBF
	5	TMPR8512RF ¹	TMPR8512RF	TMPR8512RF + TMPBPH20A
	6	TMPR8612RF ¹	TMPR8612RF	TMPR8612RF
200	2	Use TMPR8320RF with bottom blank (TCB12B)	TMPR8220RF	TMPR8220RF + TMPBPH20A
	3	TMPR8320RF ¹	TMPR8320RF	TMPR8320RF + TMPBPH20A
	4	TMPR8420RF ¹	TMPR8420RF	TMPR8420RHBF
	5	If allowed, use Ringless TMPR8520RF	TMPR8520RF	TMPR8520RF + TMPBPH20A

Single phase 1200A horizontal bussing 125 & 200A sockets—MEG approved

Socket amps	No. of sockets	Ordering code		
		Ring type socket (4 jaw socket standard)	Ringless type socket (5th jaw socket standard)	Ringless type socket (5th jaw socket standard) horned bypass factory installed
125	4	Use TMP12420RF	TMPR12412RF	TMPR12412RHBF
	5	If allowed, use Ringless TMPR12512RF	TMPR12512RF	TMPR12512RHBF
	6	If allowed, use Ringless TMPR12612RF	TMPR12612RF	Use TMPR12612RF + TMPBPH20A
200	4	TMP12420RF ¹	TMPR12420RF	TMPR12420RHBF
	5	If allowed, use Ringless TMPR12520RF	TMPR12520RF	Use TMPR12520RF + TMPBPH20A

NOTE: These MEG approved units have an added cotter pin that eliminates failure of the metering stabs when the meter is plugged into the meter base.

¹One snap-type, aluminum sealing ring (TSR5) per socket included