PLS V 7W HYB GX23 TITANIUM LED SERIES











- U HYBrid installation DIRect or BYPass
- Compatible with magnetic ballasts DIRect installation
- Built-in universal voltage driver BYPass installation
- U High efficacy 81 LPW
- Lasts 4 times longer than CFL
- Available in 2700K, 3000K, 3500K & 4000K CCT

























PLS PRODUCT FEATURES

CFL Replacement - HYBrid Installation

The PLS V blends innovative design with the latest in LED technology. The GREEN CREATIVE PLS V is the only CFL GX23 base replacement designed for vertical applications. This lamp operates on existing 13W magnetic ballasts or on 120-277V line voltage.





Fully Round Design - Patent Pending








The PLS V lamp features a patent pending fully round design. Compared to other PLS lamps, the GREEN CREATIVE PLS V improves the overall light output and aesthetics of the fixture, especially in cans.

PLS V 7W HYB GX23 TITANIUM LED SERIES









Base: GX23 (2-pin CFL)


Voltage: Magnetic ballast compatible

120-277V

Dimmable: No

PF: 0.9

Lifetime: 50,000 hrs Weight: 0.16lb / 73g



SPECIFICATIONS*

Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
57931	7	Soft White 2700K	80	550	79	120°
57932	7	Warm White 3000K	80	550	79	120°
57933	7	Neutral White 3500K	80	560	80	120°
57934	7	Cool White 4000K	80	570	81	120°
	57931 57932 57933	57931 7 57932 7 57933 7	57931 7 Soft White 2700K 57932 7 Warm White 3000K 57933 7 Neutral White 3500K	57931 7 Soft White 2700K 80 57932 7 Warm White 3000K 80 57933 7 Neutral White 3500K 80	57931 7 Soft White 2700K 80 550 57932 7 Warm White 3000K 80 550 57933 7 Neutral White 3500K 80 560	57931 7 Soft White 2700K 80 550 79 57932 7 Warm White 3000K 80 550 79 57933 7 Neutral White 3500K 80 560 80

^{*} Specification data is preliminary and subject to change

Ref.#:DS129-PLSV-7W-GX23-HYB

^{**} Suitable for damp locations. Not for use where directly exposed to weather or water

^{***} Not intended for use in enclosed fixtures