

ELECTRIC & BATTERY-POWERED KNOCKOUT KITS

LS50L Battery-Powered Knockout Punch Driver

**NEW
PRODUCT**
**AVAILABLE AS
BARE
TOOL**


A PRODUCT VIDEO IS
AVAILABLE. SCAN THIS QR
CODE OR VISIT:

www.youtube.com/GreenleeDEMO

- Punch holes from any angle with the 360° rotating head.
- Punches up to 6" holes in 14 gauge mild steel and 2" holes in 14 gauge stainless steel.
- Slim, compact and lightweight design for reduced fatigue and easy control.
- Automatic retraction prevents damage to punch and die.
- One trigger controls all tool functions, no additional manual work required.
- Non-slip rubber grip for firm and comfortable hold.
- LED light illuminates dark work areas.

SPECIFICATIONS

Weight (driver with battery)	5.05 lbs (2.29kg)
Maximum Punch Force	6 Tons (60kN)
Charging Time	22 min (RAL2/BL1380) or 15 min (RAL1/BL1815)
Battery Voltage	18V

CAT. NO.	UPC NO.	DESCRIPTION
LS50L11A	04951	Punching Tool Kit Includes: LS50L Battery Driver, (1) 18V Li-ion Battery, (1) 120V Battery Charger, (1) Spacer (1924AA), (1) 3/4-16 x 4 Drawstud (31872), (1) 3/8 x 4.8 Drawstud (209633)
LS50L11B	04956	Punching Tool Kit Includes: LS50L Battery Driver, (1) 18V Li-ion Battery, (1) 120V Battery Charger, (1) Spacer (1924AA), (1) 3/4-16 x 4 Drawstud (31872), (1) 3/8 x 4.8 Drawstud (209633), Slugbuster punches and dies for (1/2", 3/4", 1", 1-1/4", 1 1/2" and 2") conduit
LS50LB	01131	LS50 punch driver and case only (no battery, charger, or accessories).

Battery-Powered Knockout Punch Driver Kits Parts List

	CAT NO.	UPC NO.	DESCRIPTION	HOLE SIZE			KIT CAT./UPC NO.	
				CONDUIT & PIPE SIZE	ACTUAL		LS50L11A LS60LA11 LS60LA120	LS50L11B LS60LB11 LS60LB120
					Ø INCH	Ø MM		
PUNCHES AND DIES	721-1/2	31756	1/2" Conduit Size Slug-Buster® Punch	1/2"	7/8	0.885	22.5	✓
	14722	14722	1/2" Conduit Size Die	1/2"	7/8	0.885	22.5	✓
	721-3/4	31757	3/4" Conduit Size Slug-Buster® Punch	3/4"	—	1.115	28.3	✓
	124AV	06972	3/4" Conduit Size Die	3/4"	—	1.115	28.3	✓
	721-1	31758	1" Conduit Size Slug-Buster® Punch	1"	—	1.362	34.6	✓
	126AV	04011	1" Conduit Size Die	1"	—	1.362	34.6	✓
	721-1-1/4	31759	1-1/4" Conduit Size Slug-Buster® Punch	1-1/4"	1-11/16	1.701	43.2	✓
	128AV	04013	1-1/4" Conduit Size Die	1-1/4"	1-11/16	1.701	43.2	✓
	721-1-1/2	31760	1-1/2" Conduit Size Slug-Buster® Punch	1-1/2"	1-15/16	1.951	49.6	✓
	440AV	04061	1-1/2" Conduit Size Die	1-1/2"	1-15/16	1.951	49.6	✓
	721-2	31761	2" Conduit Size Slug-Buster® Punch	2"	2-3/8	2.416	61.5	✓
	442AV	04063	2" Conduit Size Die	2"	2-3/8	2.416	61.5	✓
DRAW STUDS AND MISC.	1614SS	30043	Draw Stud - 3/8" x 2-13/16"				✓	✓
	31872	31872	Draw Stud - 3/4" x 4-1/8"				✓	✓
	1924AA	03248	Spacer Short				✓	✓
	33967	33967	Stud Adapter - 3/8"				✓	✓

Replacement Draw Studs for Hydraulic Drivers

Replacement Draw Stud Selection Guide

Refer to the **ACTUAL SIZE PICTURES** and information below when ordering a replacement draw stud. Sizes given are diameter X length.



1557AA- 1-1/8" (28.6 mm) x 3" (76 mm)



60114 (Adapter) - 3/4" (19 mm) x 1/4" (6.35 mm) internal



33967 (Adapter) - 3/4" (19 mm) x 3/8" (9.5 mm) internal



60167 (Adapter) - 3/4" (19 mm) x 1/2" (12.7 mm) internal



1614SS- 3/8" (9.5 mm) x 2-13/16" (71 mm)



2113B - 3/4" (19.0 mm) x 5.38" (137 mm)



20963 - 3/8" (9.5 mm) to 3/4" (19.0 mm) x 4.8" (122 mm)



7212SP11 - 3/4" (19 mm) x 4.77" (121 mm)



7212SP12 *- 3/4" (19 mm) x 5.63" (143 mm)

**NEW
PRODUCT**

**NEW
PRODUCT**

*For use with 746 Hydraulic RAM