

Features and Benefits

Weatherproof Cable Reels

- Powder coated, solid steel construction
- Multi-position roller guide can be mounted in four different positions
- Ratchet lock can be disengaged in field for constant tension application
- UL Type 4X enclosure protects spring motor, junction box, slip ring assembly and cable entrance from hosedown or corrosion
- Optional pivot base allows 340° rotation of reel and increases range of cable to nearly any direction



HBL501242W
with **HBL16PB**



HBL501242W
with **HBL16PB**



HBL14PB

Weatherproof Cable Reels, 50 Ft. (15.2m)

Description	Cable Type	Amps	Volts AC	Weight Lbs. (kg)	Catalog Number
14" weatherproof reel.	#14/3 SOW-A	15	600	55 (24.9)	HBL501431W*
16" weatherproof reel.	#12/3 SOW-A	20	600	80 (36.3)	HBL501232W*
16" weatherproof reel, (white reel housing).	#12/3 SOW-A	20	600	80 (36.3)	HBL501232WM1*
16" weatherproof reel.	#12/4 SOW-A	16	600	86 (39.0)	HBL501242W*
16" weatherproof reel.	#10/3 SOW-A	25	600	86 (39.0)	HBL501032W*
16" weatherproof reel, (white reel housing).	#10/3 SOW-A	25	600	86 (39.0)	HBL501032WM1*
16" weatherproof reel.	#10/4 SOW-A	20	600	92 (41.7)	HBL501042W*

*Note: *All weatherproof cable reels are supplied with wire leads and 3/4" NPT hub feed. Power supply cable not supplied.*

Accessories


Description	Weight Lbs. (kg)	Description
14" pivot base.	5 (2.3)	HBL14PB
16" pivot base.	13 (5.9)	HBL16PB
Replacement stop.	.2 (.09)	HBLWPBS

Specifications

Listing/Certification	UL 355 and CSA, C22.2 No. 21.
Environment	Type 4X enclosure, CAN/CSA - C22.2 No. 21. Dry, indoor and wet and damp outdoor non-hazardous location.


Dimensions

Inch (mm)	A	B	C	D	E	F	G	H	I	J
14" Reel	6.50" (165)	8.12" (206)	16.25" (413)	13.75" (349)	3.00" (76)	12.19" (310)	3.00" (76)	3.00" (76)	3.00" (76)	6.50" (165)
16" Reel	6.50" (165)	9.12" (232)	18.25" (464)	15.75" (400)	3.00" (76)	14.19" (360)	6.00" (152)	6.00" (152)	4.94" (125)	6.50" (165)



Pivot Base

340° Pivot Base (Optional)



Note: Pivot base for use only with Weatherproof Cable Reel.

Dimensions in Inches (mm)