



## Modular Plugs

|                                                                                    | Name                                | CAT   | Type             | Feed-Thru                                                                           | Shield                                                                              | Notes                                                                                                                                                                        | Quantity                                              | Part No.       |
|------------------------------------------------------------------------------------|-------------------------------------|-------|------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|----------------|
|    | CAT6A*6/5e<br>Shielded<br>Feed-Thru | Multi | RJ-45<br>8P8C    |    |    | For shielded or unshielded CAT6A, CAT6 or CAT5e with insulated conductor diameter of 0.040" to 0.048", max. jacket diameter of .320"                                         | Card of 25                                            | <b>85-368</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Jar of 50                                             | <b>85-369</b>  |
|    | CAT6<br>Feed-Thru                   | 6     | RJ-45<br>8P8C    |    |                                                                                     | For unshielded CAT6 with 23 or 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .290"                                           | Card of 25                                            | <b>85-375</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Card of 50                                            | <b>85-376</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Bag of 100                                            | <b>85-377</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Jar of 100                                            | <b>85-377J</b> |
|    | CAT6 Single<br>Piece<br>Standard    | 6     | RJ-45<br>8P8C    |                                                                                     |                                                                                     | For unshielded CAT6 with 23 or 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .290"                                           | Card of 25                                            | <b>85-367</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Jar of 100                                            | <b>86-367J</b> |
|    | CAT6<br>3-Piece<br>Standard         | 6     | RJ-45<br>8P8C    |                                                                                     |                                                                                     | 3 piece assembly of body, sled and liner. For unshielded CAT6 with 23 or 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .290" | Card of 25                                            | <b>85-366</b>  |
|   | CAT5e<br>Feed-Thru                  | 5e    | RJ-45<br>8P8C    |   |                                                                                     | For unshielded CAT5e with 23 or 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .270"                                          | Card of 25                                            | <b>85-370</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Card of 50                                            | <b>85-371</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Bag of 100                                            | <b>85-372</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Jar of 100                                            | <b>85-372J</b> |
|  | CAT5e<br>Shielded<br>Feed-Thru      | 5e    | RJ-45<br>8P8C    |  |  | For shielded CAT5e with 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .270"                                                  | Card of 25                                            | <b>85-365</b>  |
|  | CAT5e<br>Shielded                   | 5e    | RJ-45<br>8P8C    |                                                                                     |  | For shielded CAT5e with 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .270"                                                  | Card of 25                                            | <b>85-361</b>  |
|  | CAT5e<br>Standard                   | 5e    | RJ-45<br>8P8C    |                                                                                     |                                                                                     | For unshielded CAT5e with 23 or 24 AWG conductors with a max. insulated conductor diameter of 0.041", max. jacket diameter of .270"                                          | Card of 10                                            | <b>85-147</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Card of 15<br>(includes 15<br>Strain Relief<br>Boots) | <b>85-379</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Card of 25                                            | <b>85-346</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Card of 50                                            | <b>85-396</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Bag of 100                                            | <b>86-396</b>  |
|                                                                                    |                                     |       |                  |                                                                                     |                                                                                     |                                                                                                                                                                              | Jar of 100                                            | <b>86-396J</b> |
|  | Snagless<br>Strain<br>Relief Boot   | 5e/6  | RJ-45<br>8P8C    |                                                                                     |                                                                                     | Blue colour, slide on snagless boot, max. cable diameter of 5.5mm/.220"                                                                                                      | Card of 25                                            | <b>85-380</b>  |
|  | 6-Contact<br>Voice Plug             | 3     | RJ-11/12<br>6P6C |                                                                                     |                                                                                     | 6-position, 6-contact voice grade modular plug, max. 24 AWG conductors                                                                                                       | Card of 25                                            | <b>85-345</b>  |
|  | 4 Contact<br>Voice Plug             | 3     | RJ-11<br>6P4C    |                                                                                     |                                                                                     | 6-position, 4-contact voice grade modular plug, max. 24 AWG conductors                                                                                                       | Card of 25                                            | <b>85-344</b>  |

\*only applies to a cable diameter of max. 8.1 mm with inner cores between 1.02-1.22 mm in diameter

**TO PLACE AN ORDER, PLEASE CONTACT IDEAL ON:**

Tel.: **+44 (0)1925 444 446** / Fax: **+44(0) 1925 445 501**

Email **eur.sales@idealindustries.com**

**www.idealindustriesemea.com**

## Modular Plug Termination and Prep Tools

|                                                                                                                                                                                                                |                                                                                                                                                       |                                                                                                                                                                                                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>FT-45™ Feed-Thru Modular Plug Crimp Tool</b><br><b>30-495</b><br><br><b>FT-45™ Replacement Blade</b><br><b>30-4951</b> | <br><b>Ratchet Telemaster™ Modular Plug Crimper</b><br><b>30-696</b> | <br><b>Telemaster™ Modular Plug Crimper</b><br><b>30-496</b><br><br><b>Telemaster Starter Kit</b><br><b>33-700</b> |
| <br><b>PrepPRO® UTP/Coax Cable Stripper</b><br><b>45-605</b>                                                                  | <br><b>Adjustable Ringer Jacket Stripper</b><br><b>45-165</b>        | <br><b>Electrician's Scissors</b><br><b>35-088</b>                                                                 |
| <br><b>Kinetic Super™ Wire Stripper/Crimper Kit (includes x25 UR-1 3 Wire Butt Splice IDCs)</b><br><b>33-719</b>             | <br><b>Data T®-Cutter</b><br><b>45-074</b>                          | <br><b>Data/Voice Modular Plug Crimp Kit</b><br><b>33-396</b>                                                     |

## Connector & Tool Compatibility Chart

| IDEAL CONNECTOR                     | 30-495<br>FT-45™ | 30-696<br>Ratchet<br>Telemaster™ | 30-496<br>Telemaster™ | 33-396 Data/<br>Voice Crimper |
|-------------------------------------|------------------|----------------------------------|-----------------------|-------------------------------|
| CAT6A/6/5e Shielded Feed-Thru RJ-45 | ■                |                                  |                       |                               |
| CAT6 Feed-Thru RJ-45                | ■                |                                  |                       |                               |
| CAT6 Single Piece Standard RJ-45    | ■                | ■                                | ■                     | ■                             |
| CAT6 3-Piece Standard RJ-45         | ■                | ■                                | ■                     | ■                             |
| CAT5e Feed-Thru RJ-45               | ■                |                                  |                       |                               |
| CAT5e Shielded RJ-45                | ■                | ■                                | ■                     | ■                             |
| CAT5e Shielded Feed-Thru RJ-45      | ■                |                                  |                       |                               |
| CAT5e Standard RJ-45                | ■                | ■                                | ■                     | ■                             |
| RJ-11/12 Voice Plug                 |                  | ■                                | ■                     | ■                             |
| RJ-11 Voice Plug                    |                  | ■                                | ■                     | ■                             |

**TO PLACE AN ORDER, PLEASE CONTACT IDEAL ON:**

Tel.: **+44 (0)1925 444 446** / Fax: **+44(0) 1925 445 501**

Email **eur.sales@idealindustries.com**

**www.idealindustriesemea.com**