



SAFETY COLOR CODING GUIDE		
Based on the original OSHA code.		
	EMERGENCY	Use RED for the identification of fire protection equipment and apparatus, danger and stop.
	WARNING	Use ORANGE for designating dangerous parts of machines or energized equipment that may cut, crush, shock, or otherwise injure, and to emphasize such hazards when enclosure doors are open or removed, or when gear, belt or other guards around moving equipment are open or removed, exposing unguarded hazards.
	CAUTION	Use YELLOW for designating caution and for marking physical hazards such as striking against, stumbling, falling, tripping and "caught in between." Solid yellow, and yellow with black stripes or checkers should be used interchangeably, using the combination that will attract the most attention in the particular area.
	SAFETY EQUIPMENT	Use GREEN or similar color for designating safety and the location of first aid equipment (other than firefighting equipment). Green background with a white cross is accepted as identifying first aid equipment.
	SAFETY INFORMATION	Use BLUE for identification of safety information used on informational signs and bulletin boards. In railroad areas only, blue shall be the color for designating caution, limited to warning against the starting, the use or the movement of equipment under repair or being worked on.
	TRAFFIC HOUSEKEEPING	Use BLACK & WHITE to designate traffic and housekeeping markings. Solid white, solid black, single-color striping, alternate stripes of black and white, or black and white checkers should be used in accordance with local conditions. (Purple, gray and brown may be used to accentuate color contrast and make other colors more visible).

IDENTIFICATION OF PIPING SYSTEMS		
Based on the original OSHA code.		
	FIRE PROTECTION & SPRINKLER PIPING	RED is for ANSI Class F-Fire. This classification includes sprinkler systems and other fire protection equipment.
	DANGEROUS MATERIALS	YELLOW is for ANSI Class D. This group includes materials that are hazardous to life or property because they are easily ignited, toxic, corrosive at high temperatures and pressures, produce poisonous gas or are themselves poisonous.
	SAFE MATERIALS	GREEN is for ANSI Class S. This group includes those materials involving little or no hazard to life or property in their handling.
	PROTECTIVE MATERIALS	BLUE is for ANSI Class P. This group includes materials that are piped through plants for the express purpose of being able to prevent or minimize the hazard of dangerous materials.

ECONOMY SPRAY PAINTS

COLORWORKS™ MAINTENANCE CHOICE™ ENAMEL PAINTS					
COLORS		16 oz. (11 oz. net wt.)	COLORS		16 oz. (11 oz. net wt.)
	Gloss Black	CWBK01007		Equipment Orange	CWBK01177
	Flat Black	CWBK01017		Safety Yellow	CWBK01187
	Gloss White	CWBK01027		Walnut Brown	CWBK01217
	Flat White	CWBK01037		Almond	CWBK01227
	Lt Mach Gray	CWBK01047		Silver Aluminum	CWBK01237
	Dk Mach Gray	CWBK01057		Sunshine Yellow	CWBK01267
	Industrial Gray	CWBK01067		Harvester Red	CWBK01277
	Safety Blue	CWBK01087		Citrus Yellow	CWBK01287
	Royal Blue	CWBK01097		Meadow Green	CWBK01297
	Navy Blue	CWBK01107		Zinger Pink	CWBK01327
	Safety Green	CWBK01117		Fl Jamaica Orange	CWBK01337
	Emerald Green	CWBK01127		Fl Sunset Orange	CWBK01357
	Hunter Green	CWBK01137		Clear Lacquer	CWBK01407
	Safety Red	CWBK01147		Metallic Gold	CWBK01417
	Cherry Red	CWBK01157	PRIMERS* 16 oz. (11 oz. net wt.)		
	Safety Orange	CWBK01167		Gray Primer	CWBK01247
				Red Oxide Primer	CWBK01257

Case Pack: 12

Case Pack: 12

- High paint solids formula for quality hide
 - High gloss retention
- Fast drying
 - Interior/Exterior use

WORK DAY™ ENAMEL PAINTS					
COLORS		16 oz. (10 oz. net wt.)	COLORS		16 oz. (10 oz. net wt.)
	Gloss White	A04401007		Flat Black	A04412007
	Gloss Black	A04402007		Orange	A04413007
	Blue	A04403007		Clear	A04414007
	Gloss Red	A04404007		Dark Gray	A04420007
	Gray	A04405007		Flat White	A04422007
	Yellow	A04406007		Brown	A04431007
	Gloss Pink	A04407007		True Blue	A04456007
	Green	A04408007	PRIMERS* 16 oz. (10 oz. net wt.)		
	Sky Blue	A04409007		Gray Primer	A04418007
			Red Primer	A04419007	

Case Pack: 12

- Economical
- Dries to touch in 12 minutes
- Features standard conical nozzle

*Alkyd Enamels

