

# RUST TOUGH® UTILI-COAT™ ENAMEL

Developed for the toughest environments, Utili-Coat's unique, high-solids, direct-to-metal (on new or clean metal) formulation delivers long-lasting performance.

- Premium rust-preventive enamel
- State-of-the-art corrosion protection
- One-coat coverage
- Direct-to-metal, rust-preventive formula — no primer needed
- Equipped with a standard conical actuator
- Excellent gloss and color retention

COLORS		20 oz. (15 oz. net wt.)
Utility Meter Gray (ANSI-49)		K20879007
PRIMERS		20 oz. (15 oz. net wt.)
Gray		K20829007



Case Pack: 6



# ACRYLI-QUIK™ ACRYLIC LACQUER

These paints are specifically formulated for industrial maintenance and touch-up applications. Performance is exceptional, and the broad selection includes interior/exterior acrylic lacquers, primers and specialty paints. Acryli-Quik offers high solids, fast-drying times and an excellent appearance. No Runs, No Drips, No Errors!®

- No recoat window — recoat anytime
- Dries to touch in 8 minutes
- Hard, protective, durable finish
- High-gloss finish

COLORS		16 oz. (12 oz. net wt.)	COLORS		16 oz. (12 oz. net wt.)
	Sun Yellow	K01806A07		Crystal Clear	K01301A07
	Daisy Yellow	K01813A07		Ultra-Flat Black	K01602A07
	Regal Blue	K01901A07		Semi-Flat Black	K01613A07
	True Blue (OSHA Safety Blue)	K01910A07		Gloss Black	K01601A07
	Purple	K01913A07	<b>PRIMERS (ALKYD ENAMELS) 16 oz. (12 oz. net wt.)</b>		
	Hunter Green	K02001A07		Platinum	K01314A07
	Emerald Green	K02016A07		White	K01315A07
	Cherry Red	K02101A07		Charcoal Black	K01316A07
	Banner Red	K02108A07		Ruddy Brown	K01317A07
	Safety Orange (Pumpkin)	K02411A07		Gray	K01318A07
	Leather Brown	K02501A07			
	Almond	K01506A07			
	Khaki	K02504A07			
	Pewter Gray	K01606A07			
	Stone Gray	K01605A07			
	Shadow Gray	K01604A07			
	Smoke Gray	K01608A07			
	Gloss White	K01501A07			
	Flat White	K01502A07			
	Semi-Gloss White	K01508A07			



# PRODUCT SELECTION GUIDE

PRODUCT	RUST TOUGH®	TOUGH COAT®	ACRYLI-QUIK™
Formula	Acrylic Alkyd Enamel	Acrylic Alkyd Enamel	Acrylic Lacquer Enamel
VOC/MIR Compliant	Yes	Yes	Yes
Hiding	Best	Very Good	Good
Durability	Best	Very Good	Good
Dry to the Touch	25 minutes	15 minutes	8 minutes
Recoat Window	Before 2 hours or after 48 hours	Before 2 hours or after 48 hours	Anytime (not for use over acrylics)
Cleanup	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Lacquer thinner
Corrosion Resistance	Excellent with or without primer.	Good by itself. Very good with primer.	Excellent with primer.
Gloss	High	High	High
Gasoline & Oil Resistance	Film does not soften.	Film softens after 15 minutes.	Film softens after 15 minutes.