



# CUT LEVEL 2 NITRILE DIPPED GLOVES

## MORE DURABLE. BETTER PROTECTION.



### EN388 STANDARDS

|                            |   |   |   |   |   |    |
|----------------------------|---|---|---|---|---|----|
| Abrasion                   | 1 | 2 | 3 | 4 | — | —  |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |
| Tearing                    | 1 | 2 | 3 | 4 | — | —  |
| Puncture                   | 1 | 2 | 3 | 4 | — | —  |
| Cut Resistance (TDM Test)  | A | B | C | D | E | F  |

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

**SMARTWIPE™ Touch  
Screen Compatible  
Palms & Fingertips**

**High Dexterity  
Fingertips**

**Sandy  
Nitrile Grip**

**Light &  
Breathable Back**

**Color-Coded Bands  
Easy cut level  
identification**



### SPECIFICATIONS

|                |                           |
|----------------|---------------------------|
| Gauge          | 15                        |
| Liner Material | Nylon and HPPE Blend Knit |
| Dip Material   | Sandy Nitrile             |
| Cuff Style     | Elasticated Knit          |

### RECOMMENDED APPLICATIONS

- High-Dexterity Applications
- Light Material Handling
- Finish Carpentry
- Yard Maintenance
- Plumbing

### CARE INSTRUCTIONS

Machine wash warm water (105°F),  
mild detergent, no bleach.  
Line dry.

| SIZE | 1 PAIR     | 12 PAIR (Contractor Pack) |
|------|------------|---------------------------|
| S    | 48-22-8925 | 48-22-8925B               |
| M    | 48-22-8926 | 48-22-8926B               |
| L    | 48-22-8927 | 48-22-8927B               |
| XL   | 48-22-8928 | 48-22-8928B               |
| XXL  | 48-22-8929 | 48-22-8929B               |

## SEE MORE PPE



or visit <https://qr.mke.tl/2qm6s>