

# SPECIFICATION SHEET 280-CS4200

# PIP™ 4200 SERIES CAP STYLE HARD HAT WITH SLIP RATCHET

- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) minimizes fatigue
- 4-Point suspension with HDPE strap and webbing clips provide a comfortable and secure fit
- EasyJust™ slip ratchet adjustment system with thumb and index finger points provides easy size adjustments
- Unique "3D Adjustment" provides a precise fit using harness depth settings
- Low nape strap provides a secure fit, allowing the hard hat to stay on your head even when you're looking down or bending over
- Chamlon™ sweatband made with an Egyptian cotton core and porous PU coating for maximum sweat absorption, pH neutral and dermatologically tested
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- Meets ANSI/ISEA Z89.1
- Fulfills Class E Electrical Insulation requirements
- Not compatible with the JSP® EVOSpec™ or CR2 reflective kits
- · Custom logo imprinting available on all four sides of the hard hat

#### **APPLICATIONS**

- Construction
- · Oil & gas
- Mining
- Demolition
- · High pressure jetting
- · Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

# **CARE INSTRUCTIONS**

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

# **TECHNICAL DATA**

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating					
COLOR	☐ White (-10)					
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")					
EACH WEIGHT	12.4 oz					
PACKAGING	10 per case					
CASE	23 5/8" x 9 1/2" x 16 1/8" / 60cm x 24.13cm x 40.95cm					
CASE WEIGHT	9 lbs / 4.08 kg					
C00	USA					



## **BARCODES**

ITEM	EACH	DOZEN	CASE	
☐ 280-CS4200-10	848309014522		20848309014526	
280-CS4200-20	848309014539		20848309014533	
■ 280-CS4200-30	848309014546		20848309014540	
■ 280-CS4200-50	848309014553		20848309014557	
280-CS4200-60	848309014560		20848309014564	
280-CS4200-OR	848309014577		20848309014571	

### **DIMENSIONS** (in)

	OSFA			
A	11 5/16			
В	6			

