



## PASS & SEYMOUR® Turnlok® Locking Devices Heavy-Duty Receptacles 15, 20 & 30A; 125 & 250V, 277VAC



### Quality construction for maximum durability.

4710, 4700, 4792, 4560, 4550, 4760, 4750, L520, CRL520, L620, L720, L530, CRL530, L630, L730

Choose from a broad range of capacities in both single and duplex receptacle designs. They feature high-quality, brass contacts for rock-solid electrical connections and long service life. Single-piece, solid brass or steel straps and impact-resistant nylon face and body help them shrug off hard use.

### Features & Benefits

**Compact, impact-resistant nylon face and body** are ultrasonically welded together for unrivaled strength.



**Clearly marked NEMA configuration, rating and third party listing** on each unit's face.

**One-piece, high-grade brass contacts** offer excellent conductivity and heat-rise resistance.



**Side and external screw-pressure-plate back wire capability.** Accepts #14 — #10 AWG.



**Single-piece, solid brass mounting strap** is free of easily loosened rivets found on other brands. 15 Amp mounting strap is steel.

L620-R

### 3rd Party Compliance



UL Listed, File Number E146159, Standard UL498, Attachment Plugs and Receptacles. Federal Specification WC596.  
CSA Certified, File Number LR1765, Standard CSA-C22.2 No. 42, General Use Receptacles and Attachment Plugs.  
Conforms to NEMA WD-1.

# Turnlok® Locking Devices Heavy-Duty Receptacles 15, 20 & 30A; 125 & 250V, 277VAC

## Ordering Information

Catalog Number	Ratings		Description / Color	NEMA Config.
	A	V		
Receptacles Back & Side Wire				
4710	15	125	Single Receptacle	L5-15R
4700	15	125	Duplex Receptacle	L5-15R
4792	15	125	Combination Straight Blade and Locking	5-15R and L5-15R
4560	15	250	Single Receptacle	L6-15R
4550†	15	250	Duplex Receptacle	L6-15R
4760	15	277*	Single Receptacle	L7-15R
4750	15	277*	Duplex Receptacle	L7-15R
4750	15	277*	Duplex Receptacle	L7-15R
L520R	20	125	Single Receptacle	L5-20R
CRL520R	20	125	Single Receptacle, Corrosion-Resistant	L5-20R
620R	20	250	Single Receptacle	L6-20R
L720R	20	277*	Single Receptacle	L7-20R
L530R	30	125	Single Receptacle	L5-30R
CRL530R	30	125	Single Receptacle, Corrosion-Resistant	L5-30R
L630R	30	250	Single Receptacle	L6-30R
L730R	30	277*	Single Receptacle	L7-30R

\*AC only.

†Not designed for split circuits.



**NEMA  
L5-15R**



**NEMA  
L6-15R**



**NEMA  
L7-15R**



**NEMA  
L5-20R**



**NEMA  
L6-20R**



**NEMA  
L7-20R**



**NEMA  
L5-30R**



**NEMA  
L6-30R**



**NEMA  
L7-30R**



**NEMA  
5-15R**

For more information on these and other P&S products refer to our Product Guide or visit our website.

## Technical Specifications

### Performance

#### Electrical


Dielectric Withstand Voltage	2000V minimum
Maximum Working Voltage	600VAC
Current Interrupting	Certified for current interrupting at full-rated current
Temperature Rise	30°C max. after 50 cycles at 150% rated current

#### Mechanical


Terminal Accommodation	#14 AWG min. – #10 AWG max.
Product Identification	Amperage, Voltage, NEMA Configuration molded into face
Environmental	
Flammability	UL94 V2
Operating Temperature	Maximum continuous +75°C, minimum -40°C without impact

### Materials

	Standard	Corrosion-Resistant
Front Body	Nylon	Nylon
Back Body	Nylon	Nylon
Mounting Strap	15A = Steel, 20 & 30A = Brass	Nickel-Plated Brass
Pressure Plate	Brass	Nickel-Plated Brass
Contacts	Brass	Nickel-Plated Brass
Terminal Clamps	Brass	Nickel-Plated Brass
Terminal Screws	Brass	Brass
Mounting Screws	Zinc-Plated Steel	Stainless Steel




Dimensions for 4700




Dimensions for 4792

### Warranty


1 Year




Dimensions for 4760




Dimensions for 4560




Dimensions for 4550




Dimensions for 20 Amp Receptacle



Dimensions for 30 Amp Receptacle



Dimensions for 4710



Dimensions for 4750

---

### Also available

- Light Almond Devices
  - Decorator Devices
  - Hospital Grade Devices
  - PlugTail™ Devices
  - Switches
  - Straight Blade Receptacles
  - GFCIs
  - Weatherproof Boxes & Covers
  - IEC 309 Industrial Products
  - Flexcor® Wire Mesh Grips
  - Configurable Solutions
- 



**Legrand, North America**  
60 Woodlawn Street  
West Hartford, CT 06110  
1-877-295-3472  
[www.legrand.us](http://www.legrand.us)

**Canada**  
1-844-977-3783  
[www.legrand.ca](http://www.legrand.ca)

FOLLOW US

