



# STRAIGHT BLADE RECEPTACLES

## Tamper-Resistant Commercial Grade Receptacles 15 & 20A, 125V



TR15LA



TR5252W

### Features

- Dual mechanical shutter system to help prevent insertions of foreign objects.
- Two drive screws anchor strap to back body and face where abrupt removal torque is greatest.
- .032 inch thick brass triple-wipe power contacts for lasting retention.
- Corrosion-resistant plated steel strap is locked in to the face and back body to resist pulling away from the face/body assembly.
- Auto-ground clip assures positive ground.
- Easily accessed break-off line-contact connecting tab for fast and easy split-circuit wiring.
- Backed-out tri-drive steel terminal screws.

CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.			UL498	cULus	C22.2 No. 42
<b>TAMPER-RESISTANT DUPLEX RECEPTACLES SIDE WIRE</b>							
TR15I	15	125	Ivory	5-15R	•	•	•
TR15W	15	125	White	5-15R	•	•	•
TR15	15	125	Brown	5-15R	•	•	•
TR15GRY	15	125	Gray	5-15R	•	•	•
TR15BK	15	125	Black	5-15R	•	•	•
TR15LA	15	125	Light Almond	5-15R	•	•	•
TR20I	20	125	Ivory	5-20R	•	•	•
TR20W	20	125	White	5-20R	•	•	•
TR20	20	125	Brown	5-20R	•	•	•
TR20GRY	20	125	Gray	5-20R	•	•	•
TR20BK	20	125	Black	5-20R	•	•	•
TR20LA	20	125	Light Almond	5-20R	•	•	•

CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.			UL498	FSUL WC596	C22.2 No. 42
<b>TAMPER-RESISTANT COMMERCIAL DUPLEX RECEPTACLES BACK AND SIDE WIRE</b>							
TR5252I	15	125	Ivory	5-15R	•		•
TR5252W	15	125	White	5-15R	•		•
TR5252	15	125	Brown	5-15R	•		•
TR5252GRY	15	125	Gray	5-15R	•		•
TR5252BK	15	125	Black	5-15R	•		•
TR5252LA	15	125	Light Almond	5-15R	•		•
TR5352I	20	125	Ivory	5-20R	•		•
TR5352W	20	125	White	5-20R	•		•
TR5352	20	125	Brown	5-20R	•		•
TR5352GRY	20	125	Gray	5-20R	•		•
TR5352BK	20	125	Black	5-20R	•		•
TR5352LA	20	125	Light Almond	5-20R	•		•

### 2 Pole, 3 Wire



NEMA 5-15R



NEMA 5-20R

STRAIGHT BLADE RECEPTACLES

For Bulk Packaging Solutions consult factory.