

Catalog Number 		Supply Voltage 	Nominal Power Output @ 40°F, 120V 	Nominal Power Output @ 40°F, 240V 	Outer Jacket Material 	Max Circuit Length 	Max Continuous Exposure Temperature, Power Off 
2000002864		120 V	3 W/ft		Modified Polyolefin	368 ft	185 °F
2000002611		120 V	5 W/ft		Fluoropolymer	287 ft	185 °F
2000002607		120 V	5 W/ft		Modified Polyolefin	287 ft	185 °F
2000002613		120 V	8 W/ft		Fluoropolymer	233 ft	185 °F
2000002609		120 V	8 W/ft		Modified Polyolefin	233 ft	185 °F
2000002865		208 – 277 V		3 W/ft	Modified Polyolefin	642 ft	185 °F
2000002612		208 – 277 V		5 W/ft	Fluoropolymer	584 ft	185 °F
2000002608		208 – 277 V		5 W/ft	Modified Polyolefin	584 ft	185 °F
2000002614		208 – 277 V		8 W/ft	Fluoropolymer	452 ft	185 °F
2000002610		208 – 277 V		8 W/ft	Modified Polyolefin	452 ft	185 °F
P000000794		208 – 277 V		12 W/ft	Fluoropolymer	360 ft	185 °F
P000000793		208 – 277 V		12 W/ft	Modified Polyolefin	360 ft	185 °F