

CABLE TIES - AIR HANDLING

PLENUM RATED



FEATURES

- Operating temperature minimum -40°F to maximum 185°F
- Easy grab tip for pick up from flat surfaces
- Low profile style and reduced head height increases safety, eliminates snags, cuts, and abrasions to cables, surrounding products and users
- Meets UL 1565 specifications for low smoke generation, low heat release and mechanical strength

APPLICATIONS

- Safely and easily secures wire bundles and harness components
- Air handling spaces, above drop ceilings and below raised flooring
- UL listed suitable for use in air handling spaces in accordance with the section 300.00 (c) and (d) of the National Electrical Code rules 12-010(3), (4) and (5) and 12-020 of the Canadian Electrical Code part 1

STANDARD MATERIAL

- Polyamide 6.6

CERTIFICATIONS

- Plenum AH2 Rated
- 50 & 120LB Series UL Type 21S
- Flammability rating UL 94-V2

PART #	TENSILE STRENGTH (LBS)	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	PACK	CASE QTY.
BL4MAH-C	18 LB	BURGUNDY	4.1"	0.096"	0.035"	.75"	100	10,000
BL7SAH-C	50 LB	BURGUNDY	7.6"	.18"	.054"	2"	100	5,000
BL11SAH-C	50 LB	BURGUNDY	11.1"	.18"	.054"	3"	100	5,000
BL14SAH-C	50 LB	BURGUNDY	14.6"	.18"	.054"	4"	100	5,000
BL14LAH-C	120 LB	BURGUNDY	14.6"	.298"	.069"	4"	100	2,000