

CABLE TIES - COLORED



FEATURES

- Operating temperature minimum -40°F to maximum 185°F
- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- High Yield Strength

APPLICATIONS

- Safely and easily secures wire bundles and harness components
- Colored cable ties are designed for use in general applications where unique identification is needed, while delivering ease of installation, consistent performance, and industry leading reliability

STANDARD MATERIAL

- Polyamide 6.6

CERTIFICATIONS

- Plenum AH2 Rated
- 50 & 120LB Series UL Type 21S
- Flammability rating UL 94-V2

PART #	TENSILE STRENGTH (LBS.)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BR4M(*)-C	18	INDOOR	SEE TABLE BELOW	4.1"	0.096"	0.035"	0.75"	100	1,000	6.8
BR6M(*)-C	18			6.1"	0.096"	0.05"	1.25"	100	1,000	24
BR8M(*)-C	18			8.1"	0.096"	0.05"	2.0"	100	1,000	30
BR5L(*)-C	40			5.7"	0.142"	0.05"	1.25"	100	1,000	17
BR8L(*)-C	40			8.7"	0.142"	0.05"	2.0"	100	1,000	24
BR7S(*)-C	50			7.6"	0.180"	0.055"	2.0"	100	1,000	30
BR11S(*)-C	50			11.1"	0.18"	0.054"	3.0"	100	1,000	20
BR14S(*)-C	50			14.6"	0.18"	0.054"	4.0"	100	1,000	25
BR8L(*)-C	120			9"	0.298"	0.069"	2.0"	100	1,000	21
BR11L(*)-C	120			12"	0.298"	0.069"	3.0"	100	1,000	22
BR14L(*)-C	120			14.6"	0.298"	0.069"	4.0"	100	1,000	26

*INSERT NUMBER SUFFIX FOR COLOR

SUFFIX	1	2	3	4	5	6
COLOR	BROWN	RED	ORANGE	YELLOW	GREEN	BLUE

*INSERT NUMBER SUFFIX FOR COLOR

SUFFIX	7	8	11	12	13	14	15
COLOR	PURPLE	GRAY	FLUORESCENT GREEN	FLUORESCENT PINK	FLUORESCENT YELLOW	FLUORESCENT ORANGE	FLUORESCENT BLUE

CABLE TIES - COLORED CONTINUED

PART #	TENSILE STRENGTH (LBS.)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BL4M(*)-C	18	INDOOR	SEE TABLE BELOW	4.1"	0.096"	0.035"	0.75"	100	10,000	6.8
BL4M(*)-M	18			4.1"	0.096"	0.035"	0.75"	1,000	10,000	6.8
BL6M(*)-C	18			6.1"	0.096"	0.05"	1.25"	100	20,000	24
BL6M(*)-M	18			6.1"	0.096"	0.05"	1.25"	1,000	20,000	24
BL8M(*)-C	18			8.1"	0.096"	0.05"	2.0"	100	20,000	30
BL8M(*)-M	18			8.1"	0.096"	0.05"	2.0"	1,000	20,000	30
BL5(*)-C	40			5.7"	0.142"	0.05"	1.25"	100	10,000	17
BL5(*)-M	40			5.7"	0.142"	0.05"	1.25"	1,000	10,000	17
BL8(*)-C	40			8.7"	0.142"	0.05"	2.0"	100	10,000	24
BL8(*)-M	40			8.7"	0.142"	0.05"	2.0"	1,000	10,000	24
BL7S(*)-C	50			7.6"	0.180"	0.055"	2.0"	100	10,000	30
BL7S(*)-M	50			7.6"	0.180"	0.055"	2.0"	1,000	10,000	30
BL11S(*)-C	50			11.1"	0.18"	0.054"	3.0"	100	5,000	20
BL11S(*)-M	50			11.1"	0.18"	0.054"	3.0"	1,000	5,000	20
BL14S(*)-C	50			14.6"	0.18"	0.054"	4.0"	100	5,000	25
BL14S(*)-M	50			14.6"	0.18"	0.054"	4.0"	1,000	5,000	25
BL8L(*)-C	120			9"	0.298"	0.069"	2.0"	100	2,500	21
BL11L(*)-C	120			12"	0.298"	0.069"	3.0"	100	2,000	22
BL14L(*)-C	120			14.6"	0.298"	0.069"	4.0"	100	2,000	26

*INSERT NUMBER SUFFIX FOR COLOR

SUFFIX	1	2	3	4	5	6
COLOR	BROWN	RED	ORANGE	YELLOW	GREEN	BLUE

*INSERT NUMBER SUFFIX FOR COLOR

SUFFIX	7	8	11	12	13	14	15
COLOR	PURPLE	GRAY	FLUORESCENT GREEN	FLUORESCENT PINK	FLUORESCENT YELLOW	FLUORESCENT ORANGE	FLUORESCENT BLUE