

CABLE TIES - MOUNTING HEAD



FEATURES

- Operating temperature minimum -40°F to maximum 185°F
- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- High Yield Strength

APPLICATIONS

- Safely and easily secures wire bundles and harness components
- Screw mount cable ties allow cable bundles to be secured permanently to any surface
- Ideal for communication racks, walls, or ceilings

STANDARD MATERIAL

- Polyamide 6.6 UV Resistant (Outdoor)
- Polyamide 6.6 (Indoor)

CERTIFICATIONS

- Plenum AH2 Rated
- UL Type 21
- Flammability rating UL 94-V2



PART #	TENSILE STRENGTH (LBS.)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	SCREW SIZE	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BR7SMH9-C	50	INDOOR	NATURAL	7.6"	0.180"	0.055"	2.0"	#10	100	1,000	2
BR11SMH9-C	50			11.1"	0.180"	0.055"	3.0"	#10	100	1,000	2
BR14SMH9-C	50			14.6"	0.180"	0.055"	4.0"	#10	100	1,000	3
BR14LMH9-C	120			14.6"	0.298"	0.069"	4.0"	1/4"	100	1,000	3
BR7SMH0-C	50	INDOOR / OUTDOOR	BLACK	7.6"	0.180"	0.055"	2.0"	#10	100	1,000	2
BR11SMH0-C	50			11.1"	0.180"	0.055"	3.0"	#10	100	1,000	2
BR14SMH0-C	50			14.6"	0.180"	0.055"	4.0"	#10	100	1,000	3
BR14LMH0-C	120			14.6"	0.298"	0.069"	4.0"	1/4"	100	1,000	3

PART #	TENSILE STRENGTH (LBS.)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	SCREW SIZE	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BL7SMH9-C	50	INDOOR	NATURAL	7.6"	0.180"	0.055"	2.0"	#10	100	5,000	20
BL7SMH9-M	50			7.6"	0.180"	0.055"	2.0"	#10	1,000	5,000	20
BL11SMH9-C	50			11.1"	0.180"	0.055"	3.0"	#10	100	5,000	21
BL14SMH9-C	50			14.6"	0.180"	0.055"	4.0"	#10	100	5,000	29
BL14LMH9-C	120			14.6"	0.298"	0.069"	4.0"	1/4"	100	2,000	31
BL7SMH0-C	50	INDOOR / OUTDOOR	BLACK	7.6"	0.180"	0.055"	2.0"	#10	100	5,000	20
BL7SMH0-M	50			7.6"	0.180"	0.055"	2.0"	#10	1,000	5,000	20
BL11SMH0-C	50			11.1"	0.180"	0.055"	3.0"	#10	100	5,000	21
BL14SMH0-C	50			14.6"	0.180"	0.055"	4.0"	#10	100	5,000	29
BL14LMH0-C	120			14.6"	0.298"	0.069"	4.0"	1/4"	100	2,000	31

CABLE TIES