

CABLE TIES - RELEASABLE



FEATURES

- Operating temperature minimum -40°F to maximum 185°F
- Easy to use release tab
- Low insertion for quick installation
- High Yield Strength

APPLICATIONS

- Safely and easily secures wire bundles and harness components
- Releasable cable ties are designed for use in general temporarily or permanent applications, while delivering ease of installation, consistent performance, and industry leading reliability

STANDARD MATERIAL

- Polyamide 6.6

CERTIFICATIONS

- Plenum AH2 Rated
- 50 & 120LB Series UL Type 21S
- Flammability rating UL 94-V2

PART #	TENSILE STRENGTH (LBS.)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BR7SR9-C	50	INDOOR	NATURAL	7.6"	0.18"	0.055"	2.0"	100	1,000	2
BR11SR9-C	50			11.1"	0.18"	0.055"	3.0"	100	1,000	2
BR14SR9-C	50			14.6"	0.18"	0.055"	4.0"	100	1,000	3
BR7SR0-C	50	INDOOR / OUTDOOR	BLACK	7.6"	0.18"	0.055"	2.0"	100	1,000	2
BR11SR0-C	50			11.1"	0.18"	0.055"	3.0"	100	1,000	2
BR14SR0-C	50			14.6"	0.18"	0.055"	4.0"	100	1,000	3

PART #	TENSILE STRENGTH (LBS.)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BL7SR9-C	50	INDOOR	NATURAL	7.6"	0.18"	0.055"	2.0"	100	10,000	20
BL11SR9-C	50			11.1"	0.18"	0.055"	3.0"	100	5,000	20
BL14SR9-C	50			14.6"	0.18"	0.055"	4.0"	100	5,000	25
BL7SR0-C	50	INDOOR / OUTDOOR	BLACK	7.6"	0.18"	0.055"	2.0"	100	10,000	20
BL11SR0-C	50			11.1"	0.18"	0.055"	3.0"	100	5,000	20
BL14SR0-C	50			14.6"	0.18"	0.055"	4.0"	100	5,000	25

CABLE TIES