

CABLE TIES - MILSPEC



FEATURES

- Operating temperature minimum 40°F to maximum 185°F
- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- High Yield Strength

APPLICATIONS

- Safely and easily secures wire bundles and harness components
- Screw mount cable ties allow cable bundles to be secured permanently to any surface
- Ideal for communication racks, walls, or ceilings

STANDARD MATERIAL

- Polyamide 6.6 UV Resistant (Outdoor)
- Polyamide 6.6 (Indoor)

CERTIFICATIONS

- Plenum AH2 Rated
- 50 & 120LB Series UL Type 21S
- Flammability rating UL 94-V2



MILSPEC PART #	PART #	TENSILE STRENGTH (LBS.)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
MS3367-4-9	BL4M9-M-MILSPEC	18	INDOOR	NATURAL	4.1"	0.096"	0.035"	0.75"	1,000	10,000	6.8
MS3367-5-9	BL5I9-M-MILSPEC	40			5.7"	0.142"	0.05"	1.25"	1,000	10,000	17
MS3367-1-9	BL7S9-M-MILSPEC	50			7.6"	0.180"	0.055"	2.0"	1,000	10,000	30
MS3367-7-9	BL11S9-M-MILSPEC	50			11.1"	0.18"	0.054"	3.0"	1,000	5,000	20
MS3367-2-9	BL14S9-M-MILSPEC	50			14.6"	0.18"	0.054"	4.0"	1,000	5,000	25
MS3367-3-9	BL14L9-C-MILSPEC	120			14.6"	0.298"	0.069"	4.0"	100	2,000	26
MS3367-10-9	BL24H9-L-MILSPEC	175			24.1"	0.350"	0.087"	7.2"	50	500	15
MS3367-13-9	BL36H9-L-MILSPEC	175			36"	0.350"	0.087"	11.0"	50	500	21.5
MS3367-4-(*)	BL4M(*)-M-MILSPEC	18		SEE TABLE BELOW	4.1"	0.096"	0.035"	0.75"	1,000	10,000	6.8
MS3367-5-(*)	BL5I(*)-M-MILSPEC	40			5.7"	0.142"	0.05"	1.25"	1,000	10,000	17
MS3367-1-(*)	BL7S(*)-M-MILSPEC	50			7.6"	0.180"	0.055"	2.0"	1,000	10,000	30
MS3367-7-(*)	BL11S(*)-M-MILSPEC	50			11.1"	0.18"	0.054"	3.0"	1,000	5,000	20
MS3367-2-(*)	BL14S(*)-M-MILSPEC	50			14.6"	0.18"	0.054"	4.0"	1,000	5,000	25
MS3367-3-(*)	BL14L(*)-C-MILSPEC	120			14.6"	0.298"	0.069"	4.0"	100	2,000	26
MS3367-4-0	BL4M0-M-MILSPEC	18	INDOOR / OUTDOOR	UV BLACK	4.1"	0.096"	0.035"	0.75"	1,000	10,000	6.8
MS3367-5-0	BL5I0-M-MILSPEC	40			5.7"	0.142"	0.05"	1.25"	1,000	10,000	17
MS3367-1-0	BL7S0-M-MILSPEC	50			7.6"	0.180"	0.055"	2.0"	1,000	10,000	30
MS3367-7-0	BL11S0-M-MILSPEC	50			11.1"	0.18"	0.054"	3.0"	1,000	5,000	20
MS3367-2-0	BL14S0-M-MILSPEC	50			14.6"	0.18"	0.054"	4.0"	1,000	5,000	25
MS3367-3-0	BL14L0-C-MILSPEC	120			14.6"	0.298"	0.069"	4.0"	100	2,000	26
MS3367-10-0	BL24H0-L-MILSPEC	175			24.1"	0.350"	0.087"	7.2"	50	500	15
MS3367-13-0	BL36H0-L-MILSPEC	175			36"	0.350"	0.087"	11.0"	50	500	21.5

*Insert number suffix for color

SUFFIX	1	2	3	4	5	6	7	8
COLOR	BROWN	RED	ORANGE	YELLOW	GREEN	BLUE	PURPLE	GRAY

CABLE TIES