



www.nassaunationalcable.com

SEOOW PORTABLE POWER CABLE 600V UL/CSA

Application:

- SEOOW Portable Power Cable is for use with portable tools, equipment, appliances, small motors and associated machinery where flexibility and durability are required.
- This cable is also suitable for use outdoors and for immersion in water. For applications up to 600 volts and for temperatures of -50°C to +105°C. NOTE: SEOOW is not well suited for harsh environments such as quarries, mines or gravel pits.

Conductors:

- Class K stranded soft drawn bare copper conductor per ASTM B174.

Insulation:

- Color coded premium grade Thermoplastic Elastomer (TPE).

Jacket:

- Overall jacket of black 105°C Thermoplastic Elastomer (TPE), which is oil, moisture and abrasion resistant
- Black and Yellow jackets are available

Standards:

- UL 62
- CSA C22.2 No. 49
- OSHA accepted
- Sunlight Resistant

SKU	AWG	No. of Conductors	Conductor Stranding	Nominal Insulation Thickness		Nominal Overall Diameter		Weight (lbs/kft)	Ampacity** 30°C Ambient
				Inches	mm	Inches	mm		
NNC0292X	18	2	16/30	0.030	0.76	0.342	8.69	54	10
NNC0293X	18	3	16/30	0.030	0.76	0.362	9.19	64	10
NNC0294X	18	4	16/30	0.030	0.76	0.387	9.83	79	7
NNC0295X	18	5	16/30	0.030	0.76	0.462	11.73	108	5
NNC0296X	16	2	26/30	0.030	0.76	0.367	9.32	62	13
NNC0297X	16	3	26/30	0.030	0.76	0.387	9.83	77	13
NNC0298X	16	4	26/30	0.030	0.76	0.415	10.54	91	10
NNC0299X	16	5	26/30	0.030	0.76	0.492	12.50	128	8
NNC0300X	14	2	41/30	0.045	1.14	0.497	12.62	114	18
NNC0301X	14	3	41/30	0.045	1.14	0.522	13.26	140	18
NNC0302X	14	4	41/30	0.045	1.14	0.565	14.35	166	15
NNC0303X	14	5	41/30	0.045	1.14	0.642	16.31	214	12
NNC0304X	12	2	65/30	0.045	1.14	0.570	14.48	153	25
NNC0305X	12	3	65/30	0.045	1.14	0.592	15.04	185	25
NNC0306X	12	4	65/30	0.045	1.14	0.642	16.31	227	20
NNC0307X	12	5	65/30	0.045	1.14	0.707	17.96	280	16
NNC0308X	10	2	104/30	0.045	1.14	0.617	15.67	196	30
NNC0309X	10	3	104/30	0.045	1.14	0.652	16.56	245	30
NNC0310X	10	4	104/30	0.045	1.14	0.702	17.83	301	25
NNC0311X	10	5	104/30	0.045	1.14	0.762	19.35	358	20

SKU	AWG	No. of Conductors	Conductor Stranding	Nominal Insulation Thickness		Nominal Overall Diameter		Weight (lbs/kft)	Ampacity** 30°C Ambient
				Inches	mm	Inches	mm		
NNC0312XUL	8	3	133/29	0.062	1.52	0.854	21.69	419	40
NNC0313XUL	8	4	133/29	0.060	1.52	0.940	23.88	530	35
NNC0314XUL	8	5	133/29	0.062	1.52	1.040	26.42	666	28
NNC0315XUL	6	3	133/27	0.062	1.52	0.975	24.77	579	55
NNC0316XUL	6	4	133/27	0.062	1.52	1.074	27.28	741	45
NNC0317XUL	6	5	133/27	0.062	1.52	1.185	30.10	871	36
NNC0318XUL	4	3	133/25	0.062	1.52	1.132	28.75	834	70
NNC0319XUL	4	4	133/25	0.062	1.52	1.265	32.13	1072	60
NNC0320XUL	4	5	133/25	0.062	1.52	1.385	35.18	1302	48
NNC0321XUL	2	3	666/30	0.062	1.52	1.305	33.15	1157	95
NNC0322XUL	2	4	666/30	0.062	1.52	1.455	36.96	1517	80
NNC0323XUL	2	5	666/30	0.062	1.52	1.556	39.52	1735	64

*All values are nominal and subject to correction.

📍: 505 Northern Boulevard, Suite 209, Great Neck, NY 11021

☎: (516) 482-6313, (516) 482-6438

✉: sales@nassaunationalcable.com

🌐: www.nassaunationalcable.com

NNC