

4¹¹/₁₆" Square Boxes

CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	EA. SIDE CONDUIT	EA. END CONDUIT	BOTTOM CONDUIT	STD. CTN.
<i>With Conduit KOs</i>						
72151-1/2 & 3/4-E*	1 ¹ / ₂	29.5	3- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E, 4- ¹ / ₂ "	20
72171-1/2 & 3/4-E*	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E, 3- ¹ / ₂ "	20
72171 1	2 ¹ / ₄	42.0	2-1"	2-1"	3- ¹ / ₂ " & 2- ³ / ₄ "	20
72171 3/4 1*	2 ¹ / ₄	42.0	1- ³ / ₄ " & 1-1"	1- ³ / ₄ " & 1-1"	3- ¹ / ₂ " & 3- ¹ / ₄ " & 2-1"	20
72171 1 1/4*	2 ¹ / ₄	42.0	2-1 ¹ / ₄ "	1-1 ¹ / ₄ "	3- ¹ / ₂ " & 2- ³ / ₄ "	20
72171CV 1/2 3/4*	2 ¹ / ₄	42.0	2- ¹ / ₂ " & 1- ³ / ₄ "	2- ¹ / ₂ " & 1- ³ / ₄ "	3- ¹ / ₂ " & 2- ³ / ₄ "	25
72151 MS 1/2 3/4*	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E, 3- ¹ / ₂ "	20
72151 MS 1/2 3/4	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & 2- ³ / ₄ " & 4- ¹ / ₂ "	25
72171 MS 1/2 3/4*	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E, 3- ¹ / ₂ "	25
72151MSX	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & 2- ³ / ₄ " & 4- ¹ / ₂ "	25
72151MSXP	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & ³ / ₄ "-E	2- ¹ / ₂ " & 2- ³ / ₄ " & 4- ¹ / ₂ "	25
72151MSP	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & 2- ¹ / ₂ " & ³ / ₄ "-E	25
72171MSX	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & 2- ¹ / ₂ " & ³ / ₄ "-E	25
72171MSXP	2 ¹ / ₄	42.0	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & ³ / ₄ "-E	3- ¹ / ₂ " & 2- ¹ / ₂ " & ³ / ₄ "-E	25

72171 MS 1/2 & 3/4
MS bracket for 1¹/₂", 2¹/₄", 3¹/₄", 4" metal studs

72151-1/2 & 3/4-E




72171-1/2 & 3/4-E



72171 1



72171 3/4 1



72171 1 1/4



72171CV 1/2 & 3/4

* Per UL 514-A, suitable for use without a bonding jumper in circuits above or below 250 volts.

4¹¹/₁₆" Square Boxes

CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	DESCRIPTION	CONSTRUCTION TYPE	STD. CTN.
5-SDW-FB-1	2 ¹ / ₄	42.0	Two 1" KOs in each of three sides, flat bracket on other side and three 1/2" KOs in a line in bottom with two 3/4" KOs at opposite ends in bottom. Four tapped ears*	Welded	25



5-SDW-FB-1

4¹¹/₁₆" Square Box Extension Rings


CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	KNOCKOUT (IN.)		STD. CTN.
			EA. SIDE CONDUIT	EA. END CONDUIT	
<i>With Conduit KOs</i>					
73151 1/2 3/4*	1½	29.5	2-½ 1¼	2-½ 1¼	20
73171 1/2 3/4*	2¼	42.0	2-½ 1¾	2-½ 1¼	20
73171 1	2¼	42.0	2-1	2-1	20



73151 1/2 & 3/4



73171 1/2 & 3/4




73171 1

4¹¹/₁₆" Square Covers

CAT. NO.	CU. IN. CAPACITY	RAISED (IN.)	DESCRIPTION	STD. CTN.
72 C 1	—	—	Flat blank	50
72 C 6	—	—	Flat with 1/2" KO	25
72 C 3	3.5	1/4	Center blanked	10
72-C-3-1/2	3.0	1/2	with tapped ears	25
72-C-3-3/4	4.3	3/4	on 2 ³ / ₄ " centers	10
72-C-3-1	5.8	1		25



72 C 1



72 C 6



72 C 3

www.tnb.com

United States
Tel: 901.252.8000
800.816.7809
Fax: 901.252.1354Technical Services
Tel: 888.862.3289

Thomas & Betts