SYLVANIA Lamps

LED TruWave® Selectable Lamps

Application

SYLVANIA TruWave CCT Selectable Lamps come in five different color temperature settings, letting you choose the best option to retrofit your space, all while utilizing TruWave technology.

Benefits and Features

- Each lamp comes with an option of five different CCTs (2700K, 3000K, 3500K, 4000K or 5000K)
- Toggle switch located on the lamp to easily change between CCTs (A19, A21, BR30, BR40)
- Twist the toggle located towards the base of the lamp to easily change between CCTs (PAR38)
- Mimics the natural light spectrum for improved sleep/wake cycles
- Less intense blue light for reduced eyestrain
- Excellent 90+ color rendering
- Available beam angle: 40° (PAR38 only)

Electrical

- 120VAC
- Dimmable

Rated Life

- 15,000 hours (L₇₀) for A19, A21, BR30, BR40
- 25,000 hours (L₇₀) for PAR38

Warranty

- 5 year
- NLB Trusted Warranty Program

Ambient Operating Range

- -4°F to +104°F (-20°C to +40°C) (A19, A21, BR30, BR40)
- -4°F to +113°F (-20°C to +45°C) (PAR38 only)



TruWave **Technology®**

Wattage Comparison

Traditional	Traditional	LED Wattons	Energy
Source	Wattage	Wattage	Savings
A19 Incandescent	60W	9W	85%
A21 Incandescent	100W	13W	87%
BR30 Incandescent	65W	7.5W	88%
BR40 Incandescent	85W	15W	82%
PAR38 Halogen	120W	15.5W	87%

Certifications and Listings

cULus

- FCC

cETLus

- ENERGY STAR®

RoHS

- Title 20 Tier 2 compliant



















Specification Data

Catalog #	Туре	
Project		
Comments		
Prepared by		

Ordering Guide

LED	XXX	XXXXX	DIM	9	SC3	TL	XXXXX
Product Name LED = LED Technology	Wattage 9 = 9 watts 15 = 15 watts 7.5 = 7.5 watts 13 = 13 watts 15.5 = 15.5 watts	Lamp Type A19 A21 BR30 BR40 PAR38	DIM = Dimmable	CRI 9 = 90	Color Temperature SC3 = Selectable 2700K/3000K/3500K/ 4000K/5000K	TL = TruWave®	Beam Angle FL40 = 40°Flood (PAR38 only) RP = Retail package


Ordering Information

Item	Ordering	Wattage	Base		Input Voltage	Average Rated		Typical Lumens		Power	Bulb	Case
Number	Abbreviation	(W)	Туре	Replaces	(V)	Life (hrs.)	CCT	(lm)	CRI	Factor	Finish	Qty.
42109	LED9A19DIMO9SC3RP	9	E26 Medium	60W	120	15,000	2700K/3000K/3500K/ 4000K/5000K	800	90	0.7	Plastic	8
42110	LED15A21DIM09SC3RP	15	E26 Medium	100W	120	15,000	2700K/3000K/3500K/ 4000K/5000K	1600	90	0.7	Plastic	8
41922	LED7.5BR30DIM9SC3TLRP	7.5	E26 Medium	65W	120	15,000	2700K/3000K/3500K/ 4000K/5000K	650	90	>.7	Plastic	6
42108	LED13BR40DIM9SC3RP	13	E26 Medium	85W	120	15,000	2700K/3000K/3500K/ 4000K/5000K	1100	90	0.7	Plastic	4
41522	LED15.5PAR38DIM9SC3TLFL40RP	15.5	E26 Medium	120W	120	25,000	2700K/3000K/3500K/ 4000K/5000K	1300	90	>.7	Plastic	6


Physical Information

Lamp Description	(A) Diameter in (mm)	(B) Height in (mm)
A19 CCT Select	2.36 (60)	4.64 (118)
A21 CCT Select	2.75 (70)	5.0 (128)
BR30 CCT Select	3.74 (95)	5.12 (130
BR40 CCT Select	4.72 (120)	6.25 (159)
PAR38 CCT Select	4.76 (121)	5.12 (130)












BR30



BR40



PAR38



LEDVANCE LLC 181 Ballardvale Street, Suite 203 Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks. All other trademarks are those of their respective owners. Licensee of product trademark SYLVANIA in general lighting. Specifications subject to change without notice.



SCAN TO FOLLOW US ON SOCIAL MEDIA

