

## Solar Shutdown Device Technical Specifications

The Solar Shutdown Device is a Mid-Circuit Interrupter (MCI) and is part of the PV system rapid shutdown (RSD) function in accordance with Article 690 of the applicable NEC. When paired with Tesla Solar Inverter, solar array shutdown is initiated by any loss of AC power.

Electrical Specifications	Model	MCI-1	MCI-2	MCI-2
				High Current
	Nominal Input DC Current Rating ( $I_{MP}$ )	13 A	13 A	15 A
	Maximum Input Short Circuit Current ( $I_{SC}$ )	19 A	17 A	19 A
	Maximum System Voltage (PVHCS)	600 V DC <sup>6</sup>	1000 V DC <sup>6</sup>	1000 V DC <sup>6</sup>
	Maximum Disconnect Voltage <sup>7</sup>	600 V DC	165 V DC	165 V DC
<sup>6</sup> Maximum System Voltage is limited by Tesla Solar Inverter to 600 V DC.				
<sup>7</sup> Maximum Disconnect Voltage is the maximum voltage allowed across each MCI in the open position (Rapid Shutdown Initiated). An individual MCI-2 has a voltage rating of 165V but in combination (connected in the same string) their voltage ratings are additive.				
RSD Module Performance	Maximum Number of Devices per String		5	
	Control		Power Line Excitation	
	Passive State		Normally Open	
	Maximum Power Consumption		7 W	
	Warranty		25 years	
Environmental Specifications	Operating Temperature	-40°C to 50°C (-40°F to 122°F)	-45°C to 70°C (-49°F to 158°F)	
	Storage Temperature	-30°C to 70°C (-22°F to 158°F)	-30°C to 70°C (-22°F to 158°F)	
	Enclosure Rating	NEMA 4X / IP65	NEMA 4X / IP65	
Mechanical Specifications	Electrical Connections	MC4 Connector	MC4 Connector	
	Housing	Plastic	Plastic	
	Dimensions	125 x 150 x 22 mm (5 x 6 x 1 in)	173 x 45 x 22 mm (6.8 x 1.8 x 1 in)	
	Weight	350 g (0.77 lb)	120 g (0.26 lb)	
	Mounting Options	ZEP Home Run Clip M4 Screw (#10) M8 Bolt (5/16") Nail / Wood screw	Wire Clip	
Compliance Information	Certifications	UL 1741 PVRSE, UL 3741, PVRSA (Photovoltaic Rapid Shutdown Array)		
	RSD Initiation Method	PV System AC Breaker or Switch		