

FLAT PANELS - POWER & CCT SELECTABLE



- Choose from 3 wattages and 3 color temperatures for up to 9 possible configurations
- High efficacy, up to 140 lumens per watt (LPW)
- 50,000 hours functional life (L70)
- Ambient operating temperature: -4°F to 113°F
- Steel housing with white powder coat finish
- Polystyrene lens
- Drop ceiling, suspension and surface mount options

Catalog Number	Order Code	Max Lumens	Wattage	Input Voltage	CCT	Minimum CRI	Beam Angle	Fluorescent Replacement Size	Fluorescent Replacement Wattage	DLC
PL22-35WPCTS-D	72994	3,500/4,200/4,725	25W/30W/35W	120-277V	Selectable	80	120°	2' x 2'	2x32W T8	P
PL24-50WPCTS-D	72996	4,200/5,600/6,750	30W/40W/50W	120-277V	Selectable	80	120°	2' x 4'	3x32W T8	P

Accessories (Sold Separately)

Catalog Number	Order Code	Description
F-L22/FRAME-87	70280	2' x 2' Surface Mount Frame Kit - 24" x 24" x 4"
F-L24/FRAME-87	70281	2' x 4' Surface Mount Frame Kit - 24" x 48" x 4"
F-L22/FLANGE-87	70277	2' x 2' Sheetrock Flange Kit
F-L24/FLANGE-87	70278	2' x 4' Sheetrock Flange Kit
F-L22/CABLE/BL-87	70282	4' Suspended Mount Cable Kit for use with 2' x 2' Flat Panels
F-L24/CABLE/BL-87	70283	4' Suspended Mount Cable Kit for use with 2' x 4' Flat Panels
BEL5/120-277V-92	70585	Emergency LED Driver 120-277V
WD-DS710	70605	Dimmer 0-10V



(2' x 4' Suspended Mount Cable Kit)



(Surface Mount Frame Kits)



(Sheetrock Flange Kits)

