WAC LIGHTING

Twist-N-Lite

Mini Flush Mount

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-240103	CS 2700K/3000K/3500K/4000K/5 000K - 90	12W	900	BK Black BN Brushed Nickel WT White

Example: FM-240103-CS-BK

DESCRIPTION

Quick and convenient. Easy to use and easy to install, our new Twist-N-Lite system offers a variety of surface mounts and pendant luminaires in five color temperatures and three finishes. A single flexible mounting base accommodates our complete suite of Twist-N-Lite products. The flexible design enables you to interchange the fixtures in the field to meet your various lighting applications. This energy-efficient engineering wonder offers dimmable options for high performance and a classic, minimalistic aesthetic. Select your color temperature, Twist it in and Turn it on. Elevating multifunctional illumination to a higher standard.

FEATURES

- Mount and power any fixture in the Twist-N-Lite family by twisting it onto the canopy
- All wiring and connections are made in the junction box prior to installing the mounting base and canopy
- Shared canopy allows for easily swapping between fixtures without adjusting the mounting hardware
- 5-CCT Switchable between 2700K and 5000K
- 45 deg beam angle
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction Aluminum with TIR Lens

Power: 12W

Input: 120 VAC,50/60Hz

Dimming: ELV: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED
Lens: TIR Lens
Rated Life: 50,000 Hours

Mounting: Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be

mounted on ceiling or wall in all orientations

Finish: Electrostatically Powder Coated: White, Black, Electroplated

Brushed Nickel

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Wet Location Listed, Energy Star 2.0, ADA, Title 24

JA8 Compliant



FINISHES:

Fixture Type:

Project:

Location:

Catalog Number:



LINE DRAWING:

