

8FT TYPE IA FIBERGLASS D-RUNG STRAIGHT LADDER D6208-1

SIZE	STYLE	MAX. SAFE WORKING HEIGHT	REACH HEIGHT	LOAD CAPACITY
8ft	Single Section	7ft	11ft	300lb

The D6208-1 Fiberglass One-Section 8ft Straight Ladders have non-conductive side rails and a duty rating of 300lb. Easy to transport and maneuver. Durable and long lasting. The Traction-Tred® D-rungs are slip-resistant. Durable rail shields and shoe brackets help to protect the rails from damage. The dual action feet pivot for use on hard or penetrable surfaces.

FEATURES

- Exclusive Alflo® rung joint means Twist-Proof® performance
- 1.63in slip-resistant Traction-Tred® D-rungs
- Pre-pierced holes for easy field installation of accessories
- Combination rail shield bracket and shoe with SHU-LOK® and slip-resistant pad
- Molded rung braces on bottom step for increased durability
- Mar-resistant molded end caps

SPECIFICATIONS

FEATURE	SIZE / DETAILS
Werner Benefit	Exclusive Alflo® rung joint means Twist-Proof® performance
Unique Features	Works Around Electricity
Size	8ft
Load Capacity	300lb
Duty Rating	Type IA Duty Rating
Style	Single Section
Approx. Product Length (in)	96
Approx. Product Height (in)	3
Approx. Product Width (in)	19
Approx. Product Weight (lb)	19.5

Max. Open Extended Length	8ft
Max. Safe Working Height	7ft
Number of Sections	1
Material	Fiberglass
Color of Ladder Rail	Orange
Foot Design	Shu-Lok ®, and spur plate
Foot Material	Slip-resistant pad
Approx. Product Length (ft)	8
Approx. Closed Length (in)	96
Approx. Cu. Ft. Per Unit	4.2
Section x Rungs	1 x 8
Rails Dimension	3.31in
Steps/Rung Dimension	1.625in
Base Width (in)	19 outside shoes
Fly Width	16in
Flange Dimension	1.19in
Certifications	ANSI A14.5 (2007), OSHA
Reach Height	11ft
Rung Dimension	1.625in
Rung Type	D-Rung
Approx. Shipping Length (in)	96
Max. Load	300lb
Approx. Shipping Width (in)	19
Approx. Shipping Height (in)	3
Approx. Shipping Weight (lb)	19.5