

# LIGHTING HARDWARE

For every repair or replacement need, Westinghouse has you covered. From sockets to switches, canopies to crossbars, we have the hard-to-find parts required to make your fixtures perform like new. Available in bulk and packaged.



**\*22259**  
Twin Cluster Socket  
with Male Threads on Each End  
Medium Base  
6" Wire Leads, 18 Gauge  
105° Leads  
660 Watts Max., 250 Volts  
1/4-IP Nipple  
Height - 4 1/8"



**70145**  
Horizontal Phenolic Snap-In Socket  
Fits into 7/8" x 1/4" Hole  
Medium Base  
660 Watts Max.  
250 Volts



**70407**  
Keyless Phenolic Socket  
1/4-IP Hickey  
Medium Base  
660 Watts Max.  
250 Volts



**\*22504**  
3-Way Turn-Knob Socket  
Medium Base  
250 Watts Max.  
250 Volts  
Height - 1 1/16"



**\*22381-3 Light**  
**\*22382-4 Light**  
Black Harness Set  
Candelabra Base  
Fits 3/4" Hole  
Includes Lock Nuts  
SPT-2, 18 Gauge, 105° Leads  
75 Watts Max. Per Socket, 125 Volts  
6 1/4" Between Sockets  
12" on End  
Height - 1/4"



**\*22220**  
Pigtail Socket  
24" Wire Leads  
Candelabra Base  
18-2, SPT-1  
105° Leads  
75 Watts Max.  
125 Volts  
Height - 1 1/8"



**\*22215**  
1 1/4" Snap-in Socket  
6" Wire Leads and Straight Bracket  
Medium Base  
18 Gauge, 105° Leads  
Bracket Extends 1 1/4"  
Measured Center to Center  
660 Watts Max., 250 Volts  
Height - 1 1/2"



**\*22213**  
1 1/2" Snap-in Socket  
6" Wire Leads  
Medium Base  
Fits 1 1/4" Hole  
18 Gauge  
105° Leads  
660 Watts Max., 250 Volts  
Height - 1 1/2"



**\*22217**  
9" Snap-in Socket  
9" Wire Leads  
Medium Base  
Fits 3/8" x 1/4" Hole  
18 Gauge  
105° Leads  
660 Watts Max., 250 Volts  
Height - 1 1/2"



**70413 - On/Off**  
**70421 - 2 Circuit**  
Turn-Knob Socket  
Brass Finish  
Medium Base  
Tapped 1/4-IP  
250 Watts Max., 250 Volts  
Height - 1 1/2"



**70411 - On/Off**  
**70431 - 3-Way**  
Pull Chain Socket  
Brass Finish  
Medium Base  
Tapped 1/4-IP  
250 Watts Max., 250 Volts



**\*70403 (Carded 2-Pack)**  
Two 2" Keyless Sockets  
Candelabra Base  
Threaded 1/4-IP Hickey  
75 Watts Max., 125 Volts



**\*22127**  
Adjustable Keyless Sockets  
Candelabra Base  
Threaded 1/4-IP Hickey  
75 Watts Max., 125 Volts  
Height Adjustable from 3 1/4" - 4 3/4"



**70409**  
Porcelain Keyless Socket  
Medium Base  
Threaded 1/4-IP Cap  
660 Watts Max.  
250 Volts  
Height - 2"



**\*22267**  
Porcelain Keyless Socket  
Medium Base  
1/4-IP Hickey  
660 Watts Max.  
250 Volts  
Height - 2"  
1875 Pulse Rated



**\*22370**  
**70425**  
Porcelain Fixture Socket  
Medium Base  
10" Wire Leads, Height - 2 1/2"  
1/4-IP Hickey  
18 Gauge, 105° Leads  
660 Watts Max., 250 Volts



**\*22371**  
Porcelain Fixture Socket  
Medium Base  
Height - 2"  
1/4-IP Hickey  
660 Watts Max.  
250 Volts



**\*22212**  
Porcelain Snap-In Socket  
Medium Base  
6" Wire Leads  
Fits 1 1/4" Hole  
18 Gauge, 125° Leads  
660 Watts Max., 250 Volts  
Height - 1 1/4"



**\*22212**  
Porcelain Snap-In Socket  
Medium Base  
9" Wire Leads  
Fits 3/8" x 1/4" Hole  
18 Gauge, 105° Leads  
660 Watts Max., 250 Volts  
Height - 2"



**\*22273**  
Porcelain 1-Piece Receptacle  
Medium Base  
660 Watts Max., 600 Volts  
Height - 1 1/2"  
180° C Maximum Temp.